

Multi-Visual-Inertial System: Analysis, Calibration and Estimation

Journal Title
XX(X):1–23
©The Author(s) 2021
Reprints and permission:
sagepub.co.uk/journalsPermissions.nav
DOI: 10.1177/ToBeAssigned
www.sagepub.com/

SAGE

Yulin Yang, Patrick Geneva, and Guoquan Huang

Abstract

In this paper, we study state estimation of multi-visual-inertial systems (MVIS) and develop sensor fusion algorithms to optimally fuse an arbitrary number of asynchronous inertial measurement units (IMUs) or gyroscopes and global and/or rolling shutter cameras. We are especially interested in the full calibration of the associated visual-inertial sensors, including the IMU/camera intrinsics and the IMU-IMU/camera spatiotemporal extrinsics as well as the image readout time of rolling-shutter cameras (if used). To this end, we develop a new analytic combined IMU integration with intrinsics – termed ACI³ – to preintegrate IMU measurements, which is leveraged to fuse auxiliary IMUs and/or gyroscopes alongside a base IMU. We model the multi-inertial measurements to include all the necessary inertial intrinsic and IMU-IMU spatiotemporal extrinsic parameters, while leveraging IMU-IMU rigid-body constraints to eliminate the necessity of auxiliary inertial poses and thus reducing computational complexity. By performing observability analysis of MVIS, we prove that the standard four unobservable directions remain – no matter how many inertial sensors are used, and also identify, for the first time, degenerate motions for IMU-IMU spatiotemporal extrinsics and auxiliary inertial intrinsics. In addition to the extensive simulations that validate our analysis and algorithms, we have built our own MVIS sensor rig and collected over 25 real-world datasets to experimentally verify the proposed calibration against the state-of-the-art calibration method such as Kalibr. We show that the proposed MVIS calibration is able to achieve competing accuracy with improved convergence and repeatability, which is open sourced to better benefit the community.

Keywords

Visual-inertial systems, state estimation, sensor calibration, observability analysis, degenerate motion

1 Introduction

Cameras and inertial measurement units (IMUs) have become prevalent in autonomous vehicles and mobile devices in the recent decade due to their decrease in cost and complementary sensing nature. This has led to a significant progress of developing visual-inertial navigation system (VINS) algorithms focusing on efficient and accurate pose estimation (Huang 2019). While many works have shown accurate estimation for the minimal sensing case of a single camera and IMU (Mourikis and Roumeliotis 2007; Bloesch et al. 2015; Forster et al. 2016; Qin et al. 2018; Geneva et al. 2020), it is known (Paul et al. 2017) that the inclusion of additional sensors can provide improved accuracy due to additional information and robustness to single sensor failure cases (Eckenhoff et al. 2021). Recently, multi-visual-inertial systems (MVIS) – which uses multiple IMUs and multiple cameras for 6 degree-of-freedom (DoF) pose tracking and 3D mapping – have been deployed to micro aerial vehicles (MAVs), AR/VR devices and autonomous vehicles, due to electronic sensor and compute miniaturization and thus the need for accurate calibration and state estimation methods continues to grow. We have previously investigated the single IMU-Camera case (Yang et al. 2023b), showing that even a small perturbation to calibration parameters may cause significant trajectory accuracy loss, which calls for accurate calibration of MVIS.

Regarding state estimation, many works have explored to use multiple vision sensors for better VINS performance (Leutenegger et al. 2015; Usenko et al. 2016; Paul et al. 2017; Sun et al. 2018; Campos et al. 2021; Fu et al. 2021; Kuo et al. 2020). In particular, Leutenegger et al. (2015), Usenko et al. (2016) and Fu et al. (2021) have shown that stereo camera or multiple cameras can achieve better pose accuracy or lower the uncertainties of IMU-Camera calibration. Only a few works recently investigate sensor fusion with multiple inertial sensors for VINS (Eckenhoff et al. 2019b; Zhang et al. 2020; Wu et al. 2023; Faizullin and Ferrer 2023; Kim et al. 2017), showing that the robustness and accuracy can be improved by fusing additional IMUs. For optimal fusion of multiple asynchronous visual and inertial sensors for MVIS, it is crucial to provide accurate full-calibration for these sensors, which include: (i) IMU-IMU/Camera rigid transformation, (ii) IMU-IMU/Camera time offset, (iii) IMU inertial model parameters, (iv) camera projection/distortion model parameters, and (v) image readout time of rolling shutter (RS) cameras.

Robot Perception and Navigation Group, University of Delaware, Newark, DE 19716, USA.

Corresponding author:

Yulin Yang, Department of Mechanical Engineering, University of Delaware, 130 Academy Street, Newark, DE 19716, USA.

Email: yuyang@udel.edu

While there exist literature regarding to multi-camera and multi-IMU systems (Geneva et al. 2020; Fu et al. 2021; Kim et al. 2017; Eckenhoff et al. 2021; Zhi et al. 2022; Furgale et al. 2013; Rehder et al. 2016), most of these works do not support full-calibration. For example, only synchronized multiple global shutter (GS) cameras are supported in (Geneva et al. 2020; Fu et al. 2021), which cannot handle measurements from multiple inertial sensors or rolling shutter cameras. Only extrinsic rigid transformations for multiple IMUs can be calibrated in the work of (Kim et al. 2017). Although the work (Zhi et al. 2022) can handle the spatial-temporal calibration for asynchronous cameras and IMUs, rolling shutter (RS) calibration and IMU/camera intrinsic calibration are missing. The work (Eckenhoff et al. 2021) can calibrate multiple asynchronous RS camera but the IMU intrinsic calibration is still missing. Although the work (Furgale et al. 2013) and its extension (Rehder et al. 2016) support the spatial-temporal calibration for multiple IMU/camera with intrinsics, they do not support hybrid calibration of global and rolling shutter (GS/RS) cameras. None of the aforementioned works can perform joint calibration of all the mentioned full-calibration parameters. Moreover, no observability analysis focusing on MVIS is performed, in particular, the study of the spatial-temporal calibration for IMU-IMU/gyroscope is missing from the literature, which greatly limits our understanding of the system.

To fill this gap, we first leverage IMU pre-integration (Forster et al. 2016; Eckenhoff et al. 2019a) and our previous work on analytic IMU integration (Yang et al. 2020a) to derive a new analytical IMU integrator for IMU intrinsic calibration (i.e., ACI^3). Based on this, we design a novel algorithm to fuse multiple IMU/gyroscope measurements by using the rigid body constraints between these IMUs. A complete MVIS algorithm is develop, which can truly jointly estimate all the calibration parameters (spatial-temporal parameters between IMU-IMU/camera, IMU/camera intrinsics, readout time) within a batch nonlinear least squares (NLS) optimization framework. Based on the linearized observability analysis of MVIS with full-calibration, we show that all these calibration parameters are observable given fully excited motions, and also, for the first time, identify the degenerate motions for IMU-IMU/gyroscope spatial-temporal calibration. By building our own MVIS sensor rig with multiple IMUs and GS/RS cameras for data collection, we validate the proposed system against the state-of-art Kalibr (Furgale et al. 2013; Rehder et al. 2016). In particular, the main contributions of this work are the following:

- We propose an optimization-based multi-visual-inertial (IMU and/or gyroscope) sensor calibration algorithm, which jointly estimates *all* spatial-temporal (including RS readout time) and intrinsic parameters for an arbitrary number of visual and inertial sensors.
- Building upon our prior work (Yang et al. 2020a), we develop a new analytic combined IMU integrator with intrinsics (i.e., ACI^3), which corrects both mean and covariance of pre-integrated IMU measurements when IMU bias and intrinsic linearization changes. We also propose an auxiliary IMU fusion algorithm that

allows for the both extrinsic and intrinsic calibration for multiple IMU sensors.

- We perform comprehensive observability analysis for the MVIS with full-calibration, and, for the first time, identify the degenerate motions related to IMU-IMU/gyroscope calibration. We show that under one-axis rotation motion, the rotation between IMU and gyroscope is unobservable along rotation axis. We also show that under constant local angular and linear velocity, the time offset between IMUs is observable, which counters our intuitions.
- We conduct extensive simulations with three typical motion profiles. The simulation results confirm that we are able to recover all visual and inertial calibration parameters with the proposed MVIS in the fully-excited motion case. Specifically, 25 datasets collected by our self-made sensor rig are also used for evaluating the proposed MVIS against state-of-art calibration methods, and the results prove that the proposed approach achieves comparable accuracy and better repeatability. The identified degenerate motions for the pertinent calibration parameters are also verified through both simulation and real-world experiments.

The paper is organized as follows: after briefly reviewing the related works in the next section, we present the proposed MVIS estimation framework in Section 3. The visual-inertial measurement constraints used by the system are explained in in Sections 4-7, while in Sections 8-9 we present the observability analysis and identified degenerate motions. We validate our analysis and algorithms in Sections 10-11 and conclude the paper in Section 12.

2 Related Work

While there exists rich literature in VINS (Huang 2019), in the following, we only review the works closely related to MVIS and the calibration of MVIS, which can be categorized as: (i) multiple inertial sensors aided navigation systems, (ii) multiple cameras aided inertial navigation systems, and (iii) multi-camera and multi-IMU navigation systems.

2.1 Multi-inertial navigation

There are a few works using multiple inertial sensors to improve navigation system. Wu et al. (2023) proposed to use triple IMUs with wheel encoders to improve dead reckoning and showed that the drifting rates continue dropping as the number of used IMU increases. Faizullin and Ferrer (2023) proposed to use best axes composition (BAC) algorithm to select the best fitting data from multiple inertial sensors to avoid systematic errors when fusing multiple customer grade IMUs. They showed that the inertial navigation system performances can be improved by increasing the number of used inertial sensors. Kim et al. (2017) fused multiple IMUs through reformulating pre-integration (Forster et al. 2016) by transforming the auxiliary inertial readings into the base inertial frame. However, they relied on the numerical computation of angular accelerations to perform this transformation. They did not estimate the IMU-IMU related calibration parameters, either.

Zhang et al. (2020), proposed to convert the readings from multiple IMUs into a single “virtual” synthetic IMU measurement, which is expected to be less noisy. While offering computational savings compared to other multi-inertial fusion algorithms, it relies on having perfectly known spatial-temporal calibration for these inertial sensors. It is clear that the above mentioned works all assume the high-accuracy IMU-IMU calibration is provided and they leveraged multiple IMUs but with only one camera for pose estimation. Jadid et al. (2019) showed that the fusion of three low-cost calibrated IMUs can be used to achieve similar pose tracking performances as a single high-end IMU in the application of tracking head mounted device (HMD). They also proposed to use static IMU measurements to calibrate accelerometer intrinsics and non-static IMU measurements to calibrate the gyroscope intrinsics. Lee et al. (2022) proposed an extrinsic calibration algorithm for multiple IMUs when these IMUs are rigidly connected and moving arbitrarily. Only measurements from these IMUs are needed for the calibration. However, the time offsets between these IMUs and the IMU intrinsic calibration are all missing from this work.

Although all the above mentioned works have shown that fusion of multiple IMUs to wheel-INS or VINS can improve pose tracking accuracy, most of them rely entirely or partially on high-accuracy prior calibration of these IMUs: including IMU-IMU spatial-temporal calibration and the inertial intrinsics of these IMUs. Instead, this paper aims to solve the full parameter calibration for multiple IMUs, including intrinsics, extrinsics and time offsets, especially for the application of multiple inertial sensors in VINS domain.

2.2 Multi-camera aided inertial navigation

There have been quite a few works investigating fusing observations from multiple cameras for visual-inertial navigation. Processing all the measurements from multiple cameras will significantly slow down the system. Hence, Kuo et al. (2020) proposed an information based keyframe selection algorithm for efficient multi-camera fusion. Zhang et al. (2022) proposed an efficient feature selection and tracking algorithm to speed up the measurement processing for multiple cameras. These two works only fuse visual observations from multiple cameras but without considering the sensor calibration. Fu et al. (2021) proposed to use multiple synchronized cameras to improve IMU-Camera calibration. They proved that the extrinsic covariance bound will be smaller when more cameras are used. This indicates that the IMU-Camera calibration can converge faster with more confidences. Our previous work, OpenVINS (Geneva et al. 2020) supports synchronized multiple camera aided VINS with extrinsic, intrinsic and temporal calibration between IMU and camera. However, rolling shutter cameras are not supported by either of the above works.

In this paper, the proposed MVIS supports the extrinsic and intrinsic calibration for multiple asynchronous global shutter or rolling shutter cameras. We provide quantitative analysis for how the calibration changes when 1, 2, or 3 cameras are used simultaneously. In addition, the proposed MVIS supports simultaneous calibration of global shutter and rolling shutter cameras with image readout time.

2.3 Multi-camera and multi-IMU navigation

There are only a few works focusing on joint calibration for multiple cameras and multiple IMUs. Zhi et al. (2022) proposed MultiCal, which exploits continuous-time curves to represent pose states and supports the spatial and temporal calibration for multiple IMUs and cameras with planar targets. However, rolling shutter camera calibration and IMU/camera intrinsic calibration are not supported. Eckenhoff et al. (2021) proposed a filter based framework for fusing multiple IMUs and multiple cameras by estimating each auxiliary IMU with full state (containing orientation, position, velocity, and biases), and enforced relative pose constraints between sensors at fixed rates. It also showed robustness to inertial sensor failures. This work does not take into account the inertial intrinsic parameters and only includes the IMU-IMU/camera spatial-temporal calibration. Additionally, their leveraged multi-IMU constraints required an additional 6 DoF pose for each auxiliary IMU since each IMU is propagated independently forward. Rehder et al. (2016), extended the continuous-time Kalibr framework (Furgale et al. 2013), to calibrate the extrinsic and intrinsic parameters of auxiliary inertial sensors by formulating the angular velocity and linear accelerations as functions of the trajectory spline derivatives. However, when performing IMU-camera and IMU-IMU calibration, the camera intrinsics and IMU-IMU time offset are fixed instead of jointly optimized with other parameters. It does not support visual-inertial rolling shutter calibration. In addition, no theoretical consistency analysis or 3 sigma plots for IMU intrinsic calibration are provided for validation.

Unlike the above mentioned works, the proposed MVIS supports multiple IMU/gyroscope calibrations with both global shutter and rolling shutter cameras. All related parameters, including IMU/camera intrinsics, spatial and temporal parameters between IMUs and cameras, can be calibrated. In addition, we also, for the first time, provide observability analysis, which shows that all these calibration parameters are observable given fully excited motions. We also investigate the degenerate motions that might cause certain calibration parameter to fail, especially for IMU-IMU/gyroscope spatial-temporal calibrations.

3 Multi-Visual-Inertial System

In this section, we first present the full IMU model (containing scales, axis-misalignment and gravity sensitivity) and camera model (containing camera intrinsics, lens distortion and RS readout time) in the MVIS. We then introduce the state vector containing all the calibration parameters for an arbitrary number of IMUs and cameras, followed by the nonlinear least-squares (NLS) formulation.

3.1 IMU Model

An IMU is assumed to consist of two separate frames (Yang et al. 2023b): gyroscope frame $\{w\}$ and accelerometer frame $\{a\}$. The “inertial” frame $\{I\}$ is chosen to coincide with either $\{w\}$ or $\{a\}$ (see Fig. 1). Similar to the IMU models in (Li et al. 2014; Schneider et al. 2019; Yang et al. 2023b), the raw angular velocity ${}^w\omega_m$ from the gyroscope and linear




Figure 1. The MVIS sensor frames: base IMU (IMUb) sensor composed of accelerometer frame $\{a\}$ and gyroscope $\{w\}$, base “inertial” frame $\{I\}$ is determined to coincide with gyroscope frame $\{w\}$ or accelerometer frame $\{a\}$, auxiliary IMU (IMUa) $\{I_a\}$, auxiliary gyroscope (GYRO) $\{I_g\}$, and camera (CAM) $\{C\}$ frames. The system observes environmental landmarks \mathbf{p}_f through its cameras. The system can contain arbitrary amounts of sensors.

acceleration ${}^a\mathbf{a}_m$ from accelerometer is written as:

$${}^w\boldsymbol{\omega}_m = \mathbf{T}_w {}^w\mathbf{R}^I \boldsymbol{\omega} + \mathbf{T}_g {}^I\mathbf{a} + \mathbf{b}_g + \mathbf{n}_g \quad (1)$$

$${}^a\mathbf{a}_m = \mathbf{T}_a {}^a\mathbf{R}^I \mathbf{a} + \mathbf{b}_a + \mathbf{n}_a \quad (2)$$

where \mathbf{T}_w and \mathbf{T}_a denote the scale and axis misalignment for $\{w\}$ and $\{a\}$, respectively. \mathbf{T}_g represents the gravity sensitivity. ${}^w\mathbf{R}^I$ and ${}^a\mathbf{R}^I$ denote the rotation from the gyroscope and acceleration frame to base “inertial” $\{I\}$, respectively. Note that we use 6 parameters (indexed column-wise upper/lower triangular matrix) to describe the \mathbf{T}_w and \mathbf{T}_a while \mathbf{T}_g remains a 3×3 full matrix. \mathbf{b}_g and \mathbf{b}_a are the gyroscope and accelerometer biases, which are both modeled as random walks, and \mathbf{n}_g and \mathbf{n}_a are the zero-mean Gaussian noises contaminating the measurements. The corrected angular velocity ${}^I\boldsymbol{\omega}$ and linear acceleration ${}^I\mathbf{a}$ are thus defined as:

$${}^I\boldsymbol{\omega} = {}^I\mathbf{R}\mathbf{D}_w ({}^w\boldsymbol{\omega}_m - \mathbf{b}_g - \mathbf{n}_g - \mathbf{T}_g {}^I\mathbf{a}) \quad (3)$$

$${}^I\mathbf{a} = {}^I\mathbf{R}\mathbf{D}_a ({}^a\mathbf{a}_m - \mathbf{b}_a - \mathbf{n}_a) \quad (4)$$

where $\mathbf{D}_w = \mathbf{T}_w^{-1}$ and $\mathbf{D}_a = \mathbf{T}_a^{-1}$. In practice, we consider two models in this paper: RPNG model and Kalibr model*.

- *RPNG model*: \mathbf{T}_g , ${}^I\mathbf{R}$ and \mathbf{D}_* . \mathbf{D}_* is in upper triangular matrix form as:

$$\mathbf{D}_* = \begin{bmatrix} d_{*1} & d_{*2} & d_{*4} \\ 0 & d_{*3} & d_{*5} \\ 0 & 0 & d_{*6} \end{bmatrix} \quad (5)$$

- *Kalibr model*: \mathbf{T}_g , ${}^I\mathbf{R}$ and \mathbf{D}'_* . \mathbf{D}'_* is in lower triangular matrix form as:

$$\mathbf{D}'_* = \begin{bmatrix} d_{*1} & 0 & 0 \\ d_{*2} & d_{*4} & 0 \\ d_{*3} & d_{*5} & d_{*6} \end{bmatrix} \quad (6)$$

Note that the subscript $*$ denotes either w or a . The Kalibr model is used to compare with Kalibr (Furgale et al. 2013) and benefits from assuming the inertial frame to aligned with the accelerometer. In the remaining of our analysis the RPNG model will be used.

3.2 Camera Model

Cameras follow a pinhole model as in (Geneva et al. 2020; Eckenhoﬀ et al. 2021). A 3D point feature, ${}^G\mathbf{p}_f$, is captured by a camera with visual measurement function:

$$\mathbf{z}_C = \begin{bmatrix} u & v \end{bmatrix}^\top + \mathbf{n}_C \triangleq \mathbf{h}_d(\mathbf{z}_n, \mathbf{x}_{C_{in}}) + \mathbf{n}_C \quad (7)$$

where $\{u, v\}$ is the distorted image pixel coordinate; $\mathbf{z}_n = [u_n \ v_n]^\top$ represents the normalized image pixel; \mathbf{n}_C denotes the measurement noise; $\mathbf{h}_d(\cdot)$ maps the normalized image pixel onto the image plane based on the lens distortion models and camera intrinsic parameters $\mathbf{x}_{C_{in}}$:

$$\mathbf{x}_{C_{in}} = [f_u \ f_v \ c_u \ c_v \ k_1 \ k_2 \ p_1 \ p_2]^\top \quad (8)$$

Specifically, a pinhole model ($\{f_u, f_v\}$ denotes focal length and $\{c_u, c_v\}$ the center point) with radial-tangential (*radtan*) or equivalent-distant (*equidist*) distortion.

For *radtan* distortion model, k_1 and k_2 represent the radial distortion coefficients while p_1 and p_2 are tangential distortion coefficients. We refer the reader to (OpenCV Developers Team 2021; Geneva et al. 2020) for details on the *equidist* distortion model. Note that the *radtan* model is used in the following derivations and analysis. With $\mathbf{x}_{C_{in}}$, $\mathbf{h}_d(\cdot)$, the *radtan* model is given by:

$$\begin{bmatrix} u \\ v \end{bmatrix} = \begin{bmatrix} f_u & 0 \\ 0 & f_v \end{bmatrix} \begin{bmatrix} u_d \\ v_d \end{bmatrix} + \begin{bmatrix} c_u \\ c_v \end{bmatrix} \quad (9)$$

$$\begin{bmatrix} u_d \\ v_d \end{bmatrix} = \begin{bmatrix} du_n + 2p_1u_nv_n + p_2(r^2 + 2u_n^2) \\ dv_n + p_1(r^2 + 2v_n^2) + 2p_2u_nv_n \end{bmatrix} \quad (10)$$

where $r^2 = u_n^2 + v_n^2$; $d = 1 + k_1r^2 + k_2r^4$;

GS cameras expose all pixels at a single time instance, while RS cameras expose each row sequentially. As shown by Guo et al. (2014), it may lead to large estimation errors if RS effects are not taken into account. Additionally, the camera and IMU measurement timestamps can be incorrect due to processing delays, or different clock references. To address this, we model both the time offset and camera readout time to ensure all measurements are processed in a common clock frame of reference and at the correct corresponding poses. Specifically, t_d denotes the time offset between IMU and camera timeline while t_r denotes the RS readout time for the whole image. If t denotes the time when the pixel is captured, the RS measurement function for a normalized image pixel \mathbf{z}_n is given by:

$$\mathbf{z}_n = \mathbf{h}_p \left({}^{C(t)}\mathbf{p}_f \right) \triangleq \frac{1}{Cz_f} \begin{bmatrix} Cx_f \\ Cy_f \end{bmatrix} \quad (11)$$

$$\begin{aligned} {}^{C(t)}\mathbf{p}_f &= \mathbf{h}_t({}^{I(t)}\mathbf{R}, {}^G\mathbf{p}_{I(t)}, {}^C\mathbf{R}, {}^C\mathbf{p}_I, {}^G\mathbf{p}_f) \\ &\triangleq {}^C\mathbf{R}_G^{I(t)} \mathbf{R} ({}^G\mathbf{p}_f - {}^G\mathbf{p}_{I(t)}) + {}^C\mathbf{p}_I \end{aligned} \quad (12)$$

where $\{{}^C\mathbf{R}, {}^C\mathbf{p}_I\}$ represents the rigid transformation between the IMU and camera frames. As usual, $\{{}^G\mathbf{R}, {}^G\mathbf{p}_{I(t)}\}$ is the IMU global pose corresponding to the camera measurement time t .

If the image pixel \mathbf{z}_C , Eq. (7), is captured in the m -th row (out of total M rows), and t_I is the IMU state time

*<https://github.com/ethz-asl/kalibr/wiki/Multi-IMU-and-IMU-intrinsic-calibration>

corresponding to the captured image time t_C when the first row of the image is collected, the relationship between t_I , t_C , t_d and t_r are expressed as:

$$t_I = t_C + t_d \quad (13)$$

$$t = t_I + \frac{m}{M} t_r \quad (14)$$

If the readout time $t_r = 0$, then the camera is actually a GS camera and all rows are a function of the same pose.

3.3 State Vector

The proposed MVIS can support any number of IMUs and cameras. For simplicity of presentation, we only consider one representative sensor (one base IMU, one auxiliary IMU, one auxiliary gyroscope and one RS camera) of each types in the state vector. Both simulation and real world experiments use multiple auxiliary IMUs/gyroscopes and cameras.

The state vector of the MVIS contains the base IMU inertial states \mathcal{X}_I , the auxiliary IMU states \mathcal{X}_{I_a} and the auxiliary gyro states \mathcal{X}_{I_g} from time stamp 1 to m . Additionally, it also contains all the sensor intrinsics \mathcal{X}_{In} , the spatial-temporal extrinsics \mathcal{X}_{Ex} , and the environmental features \mathcal{X}_F .

$$\mathcal{X} = [\mathcal{X}_I^\top \quad \mathcal{X}_{I_a}^\top \quad \mathcal{X}_{I_g}^\top \quad \mathcal{X}_{In}^\top \quad \mathcal{X}_{Ex}^\top \quad \mathcal{X}_F^\top]^\top \quad (15)$$

$$\mathcal{X}_I = [\mathbf{x}_{I_1}^\top \quad \mathbf{x}_{I_2}^\top \quad \cdots \quad \mathbf{x}_{I_m}^\top]^\top \quad (16)$$

$$\mathcal{X}_{I_a} = [\mathbf{x}_{I_{a1}}^\top \quad \mathbf{x}_{I_{a2}}^\top \quad \cdots \quad \mathbf{x}_{I_{am}}^\top]^\top \quad (17)$$

$$\mathcal{X}_{I_g} = [\mathbf{x}_{I_{g1}}^\top \quad \mathbf{x}_{I_{g2}}^\top \quad \cdots \quad \mathbf{x}_{I_{gm}}^\top]^\top \quad (18)$$

where \mathcal{X}_F contains 3D feature 3D positions ${}^G\mathbf{p}_{f_i}$ ($i = 1, \dots, l$):

$$\mathcal{X}_F = [{}^G\mathbf{p}_{f_1}^\top \cdots {}^G\mathbf{p}_{f_l}^\top]^\top \quad (19)$$

In (15), \mathbf{x}_I , \mathbf{x}_{I_a} and \mathbf{x}_{I_g} denote the base IMU state, auxiliary IMU state and auxiliary gyroscope state, respectively:

$$\mathbf{x}_I = [\mathbf{x}_{nav}^\top \mid \mathbf{x}_b^\top]^\top \triangleq [{}^G\bar{q}^\top \quad {}^G\mathbf{p}_I^\top \quad {}^G\mathbf{v}_I^\top \mid \mathbf{b}_g^\top \quad \mathbf{b}_a^\top]^\top \quad (20)$$

$$\mathbf{x}_{I_a} = [{}^G\mathbf{v}_{I_a}^\top \mid \mathbf{x}_{A_b}^\top]^\top \triangleq [{}^G\mathbf{v}_{I_a}^\top \mid \mathbf{b}_{A_g}^\top \quad \mathbf{b}_{A_a}^\top]^\top \quad (21)$$

$$\mathbf{x}_{I_g} = \mathbf{b}_{G_g} \quad (22)$$

where \mathbf{x}_I contains IMU navigation state \mathbf{x}_{nav} and bias state \mathbf{x}_b ; ${}^G\bar{q}$ (${}^G\bar{q}$) is Hamilton quaternion and denotes the rotation ${}^G\mathbf{R}$ (${}^G\mathbf{R}$) from the base (auxiliary) IMU frame to global frame $\{G\}$ (Yang et al. 2020a). ${}^G\mathbf{p}_I$ (${}^G\mathbf{p}_{I_a}$) and ${}^G\mathbf{v}_I$ (${}^G\mathbf{v}_{I_a}$) represent the global position and velocity of base (auxiliary) IMU in $\{G\}$. \mathbf{b}_g and \mathbf{b}_a denote the gyro and accelerometer bias for base IMU, respectively. \mathbf{b}_{A_g} and \mathbf{b}_{A_a} denote the gyro and accelerometer bias for auxiliary IMU, respectively. \mathbf{b}_{G_g} denotes the gyroscope bias for auxiliary gyroscope. Note that we did not keep a full navigation state for auxiliary IMU/gyroscope since the poses can be recovered by the rigid body transform from the based IMU.

\mathbf{x}_{In} contains base IMU intrinsics \mathbf{x}_{in} , auxiliary IMU intrinsics $\mathbf{x}_{A_{in}}$, auxiliary gyroscope intrinsics $\mathbf{x}_{G_{in}}$ and camera intrinsics $\mathbf{x}_{C_{in}}$:

$$\mathcal{X}_{In} = [\mathbf{x}_{in}^\top \quad \mathbf{x}_{A_{in}}^\top \quad \mathbf{x}_{G_{in}}^\top \quad \mathbf{x}_{C_{in}}^\top]^\top \quad (23)$$

Table 1. The full-calibration parameters in the proposed MVIS.

Sensor	Extrinsics	Temporal	Intrinsics	Qty
Base IMU	—	—	\mathbf{x}_{in}	1
Aux IMU	${}^I_a\mathbf{R}, {}^I_a\mathbf{p}_{I_a}$	t_{da}	$\mathbf{x}_{A_{in}}$	≥ 1
Aux Gyro	${}^I_g\mathbf{R}$	t_{dg}	$\mathbf{x}_{G_{in}}$	≥ 1
Camera	${}^I_C\mathbf{R}, {}^I_C\mathbf{p}_C$	t_d, t_r	$\mathbf{x}_{C_{in}}$	≥ 1

$$\mathbf{x}_{in} = [\mathbf{x}_w^\top \quad \mathbf{x}_a^\top \quad \mathbf{x}_{T_g}^\top \quad {}^I_a\bar{q}^\top]^\top \quad (24)$$

$$\mathbf{x}_{A_{in}} = [\mathbf{x}_{A_w}^\top \quad \mathbf{x}_{A_a}^\top \quad \mathbf{x}_{A_g}^\top \quad {}^I_a\bar{q}^\top]^\top \quad (25)$$

$$\mathbf{x}_{G_{in}} = \mathbf{x}_{G_w} \quad (26)$$

where \mathbf{x}_w (\mathbf{x}_{A_w}), \mathbf{x}_a (\mathbf{x}_{A_a}) contains all the 6 column-wise parameters from \mathbf{D}_w and \mathbf{D}_a for base (auxiliary) IMU, respectively. \mathbf{x}_{T_g} (\mathbf{x}_{A_g}) contains all the 9 parameters for \mathbf{T}_g and \mathbf{T}_{A_g} from base (auxiliary) IMU, respectively. ${}^I_a\bar{q}$ (${}^I_a\bar{q}$) denotes the rotation from the accelerator frame to the base (auxiliary) IMU frame. \mathbf{x}_{G_w} denotes the 6 column-wise parameters from \mathbf{D}_w for auxiliary gyroscope.

\mathcal{X}_{Ex} contains the spatial-temporal calibrations for base IMU to auxiliary IMU \mathbf{x}_{I_A} , base IMU to auxiliary gyroscope \mathbf{x}_{I_G} and base IMU to camera \mathbf{x}_{I_C} , respectively:

$$\mathcal{X}_{Ex} = [\mathbf{x}_{I_A}^\top \quad \mathbf{x}_{I_G}^\top \quad \mathbf{x}_{I_C}^\top]^\top \quad (27)$$

$$\mathbf{x}_{I_A} = [{}^I_a\bar{q}^\top \quad {}^I_a\mathbf{p}_{I_a}^\top \quad t_{da}]^\top \quad (28)$$

$$\mathbf{x}_{I_G} = [{}^I_g\bar{q}^\top \quad t_{dg}]^\top \quad (29)$$

$$\mathbf{x}_{I_C} = [{}^I_C\bar{q}^\top \quad {}^I_C\mathbf{p}_C^\top \quad t_d \quad t_r]^\top \quad (30)$$

Note that time offset between auxiliary IMU and base IMU is defined as: $t_{da} = t_a - t_I$, where t_a and t_I represent the auxiliary and base IMU measurement time, respectively. The t_{dg} and t_d are defined in similar way. t_r denotes the whole image reading out time for the RS camera. Note that all the calibration parameters are summarized in Table 1.

3.4 NLS Formulation

Given measurements from a sensor S , with additive white Gaussian noise, we have:

$$\mathbf{z}_S = \mathbf{h}_S(\mathbf{x}) + \mathbf{n}_S, \quad \mathbf{n}_S \sim \mathcal{N}(\mathbf{0}, \mathbf{R}_S) \quad (31)$$

Then, we can formulate the NLS problem as:

$$\min_{\mathbf{x}} \sum \|\mathbf{z}_S - \mathbf{h}_S(\mathbf{x})\|_{\mathbf{R}_S^{-1}}^2 \quad (32)$$

An initial guess $\hat{\mathbf{x}}^\ominus$ is needed to start the optimization. After computing the incremental state correction $\delta\mathbf{x}$, we can refine the state estimates by $\hat{\mathbf{x}}^\oplus = \hat{\mathbf{x}}^\ominus \boxplus \delta\mathbf{x}$, where \boxplus represents the state manifold update (Barfoot 2017). In summary, we have the following NLS equivalent to maximum likelihood estimation (MLE) under some common assumptions:

$$\min_{\mathbf{x}} \sum \mathbb{C}_I + \sum \mathbb{C}_{I_a} + \sum \mathbb{C}_{I_g} + \sum \mathbb{C}_C \quad (33)$$

where \mathbb{C}_I , \mathbb{C}_{I_a} , \mathbb{C}_{I_g} and \mathbb{C}_C denotes the cost for base IMU, auxiliary IMU, auxiliary gyroscope, and camera, respectively, and will be built explicitly later. Solving this problem via iterative algorithms [e.g., GTSAM (Dellaert 2012)] yields the optimal IMU states, point features, and full-calibration parameters [see (15)].

4 ACI³: Preintegration with Intrinsic

In this section, we extend our analytic combined IMU integration (ACI²) (Yang et al. 2020a) to incorporate IMU intrinsic into preintegration, and propose an efficient IMU integrator that can be leveraged for IMU intrinsic calibration.

The IMU dynamic model is given by (Trawny and Roumeliotis 2005; Sola 2017):

$$\begin{aligned} {}^G_I \dot{\bar{q}} &= \frac{1}{2} \Omega({}^I \omega) \cdot {}^G_I \bar{q}, \quad {}^G_I \dot{\mathbf{p}}_I = {}^G \mathbf{v}_I \\ {}^G_I \dot{\mathbf{v}}_I &= {}^G_I \mathbf{R}^T \mathbf{a} + {}^G \mathbf{g}, \quad {}^I \dot{\mathbf{b}}_g = \mathbf{n}_{wg}, \quad {}^I \dot{\mathbf{b}}_a = \mathbf{n}_{wa} \end{aligned} \quad (34)$$

where ${}^G \mathbf{g} = [0 \ 0 \ -9.81]^\top$, \mathbf{n}_{wg} and \mathbf{n}_{wa} are the white Gaussian noises driving the gyroscope and accelerometer biases. $\Omega(\omega) := \begin{bmatrix} 0 & -\omega^\top \\ \omega & -[\omega] \end{bmatrix}$ and $[\cdot]$ represents a skew symmetric matrix. We also denote $\hat{\mathbf{x}}$ as estimate of \mathbf{x} while $\tilde{\mathbf{x}}$ as error states between \mathbf{x} and $\hat{\mathbf{x}}$, i.e., $\tilde{\mathbf{x}} = \mathbf{x} - \hat{\mathbf{x}}$. Note that we have a special definition for the rotation error states as:

$$\delta \bar{q} = \hat{q}^{-1} \otimes \bar{q} \Rightarrow \exp(\delta \theta) = \hat{\mathbf{R}}^\top \mathbf{R}$$

where \otimes denotes the quaternion operation (Sola 2017) and $\exp(\delta \theta) \simeq \mathbf{I}_3 + [\delta \theta]$.

4.1 Preintegration Terms

Between two sampling times t_k and t_j , we integrate the IMU dynamic model as follows:

$${}^G_{I_j} \mathbf{R} = {}^G_{I_k} \mathbf{R} \cdot \Delta \mathbf{R} \quad (35)$$

$${}^G_{I_j} \mathbf{p}_{I_j} = {}^G_{I_k} \mathbf{p}_{I_k} + {}^G \mathbf{v}_{I_k} \delta t_k + {}^G_{I_k} \mathbf{R} \Delta \mathbf{p} + \frac{1}{2} {}^G \mathbf{g} \delta t_k^2 \quad (36)$$

$${}^G_{I_j} \mathbf{v}_{I_j} = {}^G_{I_k} \mathbf{v}_{I_k} + {}^G_{I_k} \mathbf{R} \Delta \mathbf{v} + {}^G \mathbf{g} \delta t_k \quad (37)$$

$$\mathbf{b}_{g_j} = \mathbf{b}_{g_k} + \Delta \mathbf{b}_g \quad (38)$$

$$\mathbf{b}_{a_j} = \mathbf{b}_{a_k} + \Delta \mathbf{b}_a \quad (39)$$

where $\delta t = t_j - t_k$, while $\Delta \mathbf{R}$, $\Delta \mathbf{p}$, $\Delta \mathbf{v}$, $\Delta \mathbf{b}_g$, and $\Delta \mathbf{b}_a$ are the IMU preintegration terms from t_k to t_j , defined by:

$$\begin{bmatrix} \Delta \mathbf{R} \\ \Delta \mathbf{p} \\ \Delta \mathbf{v} \\ \Delta \mathbf{b}_g \\ \Delta \mathbf{b}_a \end{bmatrix} \triangleq \begin{bmatrix} \exp \left(\int_{t_k}^{t_j} I_\tau \omega d\tau \right) \\ \int_{t_k}^{t_j} \int_{t_k}^s I_\tau \mathbf{R}^T \mathbf{a} d\tau ds \\ \int_{t_k}^{t_j} \int_{t_k}^s I_\tau \mathbf{R}^T \mathbf{a} d\tau \\ \int_{t_k}^{t_j} \mathbf{n}_{wg} d\tau \\ \int_{t_k}^{t_j} \mathbf{n}_{wa} d\tau \end{bmatrix} = \begin{bmatrix} \mathbf{h}_R(\mathbf{x}_{I_k}, \mathbf{x}_{I_j}) \\ \mathbf{h}_p(\mathbf{x}_{I_k}, \mathbf{x}_{I_j}) \\ \mathbf{h}_v(\mathbf{x}_{I_k}, \mathbf{x}_{I_j}) \\ \mathbf{b}_{g_j} - \mathbf{b}_{g_k} \\ \mathbf{b}_{a_j} - \mathbf{b}_{a_k} \end{bmatrix} \quad (40)$$

where we have defined:

$$\mathbf{h}_R(\mathbf{x}_{I_k}, \mathbf{x}_{I_j}) \triangleq {}^G_{I_k} \mathbf{R}^\top {}^G_{I_j} \mathbf{R} \quad (41)$$

$$\mathbf{h}_p(\mathbf{x}_{I_k}, \mathbf{x}_{I_j}) \triangleq {}^G_{I_k} \mathbf{R}^\top \left({}^G_{I_j} \mathbf{p}_{I_j} - {}^G_{I_k} \mathbf{p}_{I_k} - {}^G \mathbf{v}_{I_k} \delta t - \frac{1}{2} {}^G \mathbf{g} \delta t^2 \right) \quad (42)$$

$$\mathbf{h}_v(\mathbf{x}_{I_k}, \mathbf{x}_{I_j}) \triangleq {}^G_{I_k} \mathbf{R}^\top \left({}^G_{I_j} \mathbf{v}_{I_j} - {}^G_{I_k} \mathbf{v}_{I_k} - {}^G \mathbf{g} \delta t \right) \quad (43)$$

In the following, the proposed ACI³ recursively computes the mean and covariance of these preintegrated terms (i.e., $\Delta \mathbf{R}$, $\Delta \mathbf{p}$, $\Delta \mathbf{v}$, $\Delta \mathbf{b}_g$ and $\Delta \mathbf{b}_a$) with intrinsic \mathbf{x}_{in} .

4.2 Recursive Formulation

Assuming $j - k + 1$ IMU readings between the timestamps k and j , there exists an integer i such that: $k \leq k + i < k + i + 1 \leq j$. $\Delta \mathbf{R}_i$, $\Delta \mathbf{p}_i$ and $\Delta \mathbf{v}_i$ denote the integration components using all IMU readings from time t_k to t_{k+i} :

$$\Delta \mathbf{R}_i = \exp \left(\int_{t_k}^{t_{k+i}} I_\tau \omega d\tau \right) \quad (44)$$

$$\Delta \mathbf{p}_i = \int_{t_k}^{t_{k+i}} \int_{t_k}^s I_\tau \mathbf{R}^T \mathbf{a} d\tau ds \quad (45)$$

$$\Delta \mathbf{v}_i = \int_{t_k}^{t_{k+i}} I_\tau \mathbf{R}^T \mathbf{a} d\tau \quad (46)$$

$$\Delta \mathbf{b}_{gi} = \mathbf{b}_{g_{k+i}} - \mathbf{b}_{g_k} \quad (47)$$

$$\Delta \mathbf{b}_{ai} = \mathbf{b}_{a_{k+i}} - \mathbf{b}_{a_k} \quad (48)$$

With that, we compute the preintegration in the following recursive form:

$$\Delta \mathbf{R}_{i+1} = \Delta \mathbf{R}_i \cdot \mathbf{R}_{i,i+1} \quad (49)$$

$$\Delta \mathbf{p}_{i+1} = \Delta \mathbf{p}_i + \Delta \mathbf{v}_i \delta t_i + \Delta \mathbf{R}_i \cdot \mathbf{p}_{i,i+1} \quad (50)$$

$$\Delta \mathbf{v}_{i+1} = \Delta \mathbf{v}_i + \Delta \mathbf{R}_i \cdot \mathbf{v}_{i,i+1} \quad (51)$$

$$\Delta \mathbf{b}_{gi+1} = \Delta \mathbf{b}_{gi} + \mathbf{b}_{gi,i+1} \quad (52)$$

$$\Delta \mathbf{b}_{ai+1} = \Delta \mathbf{b}_{ai} + \mathbf{b}_{ai,i+1} \quad (53)$$

where the increments are defined as:

$$\mathbf{R}_{i,i+1} = I_{k+i+1} \mathbf{R} = \exp \left(\int_{t_{k+i}}^{t_{k+i+1}} I_\tau \omega d\tau \right) \quad (54)$$

$$\mathbf{p}_{i,i+1} = \int_{t_{k+i}}^{t_{k+i+1}} \int_{t_{k+i}}^s I_\tau \mathbf{R}^T \mathbf{a} d\tau ds \quad (55)$$

$$\mathbf{v}_{i,i+1} = \int_{t_{k+i}}^{t_{k+i+1}} I_\tau \mathbf{R}^T \mathbf{a} d\tau \quad (56)$$

$$\mathbf{b}_{gi,i+1} = \int_{t_{k+i}}^{t_{k+i+1}} \mathbf{n}_{wg} d\tau \quad (57)$$

$$\mathbf{b}_{ai,i+1} = \int_{t_{k+i}}^{t_{k+i+1}} \mathbf{n}_{wa} d\tau \quad (58)$$

By applying (49)-(53) to all the IMU readings from t_k to t_j , we can compute both the mean and covariance of the IMU preintegration terms (i.e., $\Delta \mathbf{R}$, $\Delta \mathbf{p}$, $\Delta \mathbf{v}$, $\Delta \mathbf{b}_g$ and $\Delta \mathbf{b}_a$), as derived in what follows.

4.3 Mean Prediction

To simplify the ensuring derivations, we rewrite the IMU readings ω_{k+i} and \mathbf{a}_{k+i} as:

$$\omega_{k+i} = \hat{\omega}_{k+i} + \tilde{\omega}_{k+i} \quad (59)$$

$$\mathbf{a}_{k+i} = \hat{\mathbf{a}}_{k+i} + \tilde{\mathbf{a}}_{k+i} \quad (60)$$

where $\tilde{\omega}_{k+i}$ and $\tilde{\mathbf{a}}_{k+i}$ are the error terms that contain IMU noises as defined in Appendix A. With (47) and (48), $\hat{\omega}_{k+i}$ and $\hat{\mathbf{a}}_{k+i}$ are computed as [see (3) and (4)]:

$$\hat{\omega}_{k+i} = I_w \hat{\mathbf{R}} \hat{\mathbf{D}}_w \left({}^w \omega_{m_{k+i}} - \Delta \hat{\mathbf{b}}_{gi} - \hat{\mathbf{b}}_{gk} - \hat{\mathbf{T}}_g \hat{\mathbf{a}}_{k+i} \right) \quad (61)$$

$$\hat{\mathbf{a}}_{k+i} = I_a \hat{\mathbf{R}} \hat{\mathbf{D}}_a \left({}^a \mathbf{a}_{m_{k+i}} - \Delta \hat{\mathbf{b}}_{ai} - \hat{\mathbf{b}}_{ak} \right) \quad (62)$$

Assuming that $\hat{\omega}_{k+i}$ and $\hat{\mathbf{a}}_{k+i}$ are constant during the IMU sampling interval $[t_{k+i}, t_{k+i+1}]$, we have:

$$\hat{\mathbf{R}}_{i,i+1} = \exp(\hat{\omega}_{k+i} \delta t_i) \quad (63)$$

$$\hat{\mathbf{p}}_{i,i+1} = \int_{t_{k+i}}^{t_{k+i+1}} \int_{t_{k+i}}^s \frac{I_{k+i}}{I_r} \hat{\mathbf{R}} d\tau ds \cdot \hat{\mathbf{a}}_{k+i} \triangleq \Xi_2 \cdot \hat{\mathbf{a}}_{k+i} \quad (64)$$

$$\hat{\mathbf{v}}_{i,i+1} = \int_{t_{k+i}}^{t_{k+i+1}} \frac{I_{k+i}}{I_r} \hat{\mathbf{R}} d\tau \cdot \hat{\mathbf{a}}_{k+i} \triangleq \Xi_1 \cdot \hat{\mathbf{a}}_{k+i} \quad (65)$$

$$\hat{\mathbf{b}}_{gi,i+1} = \mathbf{0}_{3 \times 1}, \quad \hat{\mathbf{b}}_{ai,i+1} = \mathbf{0}_{3 \times 1} \quad (66)$$

where Ξ_1 and Ξ_2 are defined as follows:

$$\Xi_1 = \int_{t_{k+i}}^{t_{k+i+1}} \frac{I_{k+i}}{I_r} \hat{\mathbf{R}} d\tau \quad (67)$$

$$\Xi_2 = \int_{t_{k+i}}^{t_{k+i+1}} \int_{t_{k+i}}^s \frac{I_{k+i}}{I_r} \hat{\mathbf{R}} d\tau ds \quad (68)$$

We thus recursively compute the IMU preintegration mean:

$$\Delta \hat{\mathbf{R}}_{i+1} = \Delta \hat{\mathbf{R}}_i \cdot \hat{\mathbf{R}}_{i,i+1} \quad (69)$$

$$\Delta \hat{\mathbf{p}}_{i+1} = \Delta \hat{\mathbf{p}}_i + \Delta \hat{\mathbf{v}}_i \delta t_i + \Delta \hat{\mathbf{R}}_i \cdot \hat{\mathbf{p}}_{i,i+1} \quad (70)$$

$$\Delta \hat{\mathbf{v}}_{i+1} = \Delta \hat{\mathbf{v}}_i + \Delta \hat{\mathbf{R}}_i \cdot \hat{\mathbf{v}}_{i,i+1} \quad (71)$$

$$\Delta \hat{\mathbf{b}}_{gi+1} = \Delta \hat{\mathbf{b}}_{gi} + \hat{\mathbf{b}}_{gi,i+1} \quad (72)$$

$$\Delta \hat{\mathbf{b}}_{ai+1} = \Delta \hat{\mathbf{b}}_{ai} + \hat{\mathbf{b}}_{ai,i+1} \quad (73)$$

4.4 Covariance Prediction

To compute the covariance of the preintegration measurements, we need to obtain the state transition matrix and noise Jacobians of the recursive formulation by linearizing the three preintegration terms [see Eq. (49)-(51)]:

$$\mathbf{R}_{i,i+1} = \hat{\mathbf{R}}_{i,i+1} \tilde{\mathbf{R}}_{i,i+1} \quad (74)$$

$$= \hat{\mathbf{R}}_{i,i+1} \exp\left(\mathbf{J}_r(\hat{\theta}_{i,i+1}) \tilde{\omega}_{k+i} \delta t_i\right) \quad (75)$$

$$\mathbf{p}_{i,i+1} = \hat{\mathbf{p}}_{i,i+1} + \tilde{\mathbf{p}}_{i,i+1} \quad (76)$$

$$= \hat{\mathbf{p}}_{i,i+1} - \Xi_4 \tilde{\omega}_{k+i} + \Xi_2 \tilde{\mathbf{a}}_{k+i} \quad (77)$$

$$\mathbf{v}_{i,i+1} = \hat{\mathbf{v}}_{i,i+1} + \tilde{\mathbf{v}}_{i,i+1} \quad (78)$$

$$= \hat{\mathbf{v}}_{i,i+1} - \Xi_3 \tilde{\omega}_{k+i} + \Xi_1 \tilde{\mathbf{a}}_{k+i} \quad (79)$$

where $\hat{\theta}_{i,i+1} = \hat{\omega}_{k+i} \delta t_i$ and $\mathbf{J}_r(\hat{\theta}_{i,i+1}) \triangleq \mathbf{J}_r(\hat{\omega}_{k+i} \delta t_i)$ denotes the right Jacobian of $\mathcal{SO}(3)$ (Chirikjian 2011). The integrated components Ξ_3 and Ξ_4 are defined as:

$$\Xi_3 \triangleq \int_{t_{k+i}}^{t_{k+i+1}} \frac{I_{k+i}}{I_r} \mathbf{R}[\hat{\mathbf{a}}_{k+i}] \mathbf{J}_r(\hat{\omega}_{k+i} \delta \tau) \delta \tau d\tau \quad (80)$$

$$\Xi_4 \triangleq \int_{t_{k+i}}^{t_{k+i+1}} \int_{t_{k+i}}^s \frac{I_{k+i}}{I_r} \mathbf{R}[\hat{\mathbf{a}}_{k+i}] \mathbf{J}_r(\hat{\omega}_{k+i} \delta \tau) \delta \tau d\tau ds \quad (81)$$

The IMU preintegration errors are given by:

$$\tilde{\mathbf{z}}_{I_i} = [\delta \Delta \theta_i^\top \quad \Delta \tilde{\mathbf{p}}_i^\top \quad \Delta \tilde{\mathbf{v}}_i^\top \quad \Delta \tilde{\mathbf{b}}_{gi}^\top \quad \Delta \tilde{\mathbf{b}}_{ai}^\top]^\top \quad (82)$$

With that, the linearized IMU preintegration becomes:

$$\tilde{\mathbf{z}}_{I_{i+1}} = \Phi_{i,i+1} \tilde{\mathbf{z}}_{I_i} + \Phi_b \tilde{\mathbf{x}}_{b_k} + \Phi_{in} \tilde{\mathbf{x}}_{in} + \mathbf{G}_i \mathbf{n}_{dI} \quad (83)$$

where $\Phi_{i+1,i}$, Φ_b , Φ_{in} and \mathbf{G}_i are given in Appendix B. Finally, the measurement covariance \mathbf{Q}_I follows the following recursive form:

$$\mathbf{Q}_{I_{i+1}} = \Phi_{i+1,i} \mathbf{Q}_{I_i} \Phi_{i+1,i}^\top + \mathbf{G}_i \mathbf{Q}_d \mathbf{G}_i^\top \quad (84)$$

By repeating the above equation, we have the preintegrated IMU measurement covariance between t_k and t_j .

5 Base Inertial Costs

Since IMU intrinsics and biases are needed for IMU integration, $\Delta \mathbf{R}$, $\Delta \mathbf{p}$ and $\Delta \mathbf{v}$ are also functions of \mathbf{x}_{in} and \mathbf{x}_b . In order to avoid re-integration and re-linearization in iterative solvers when the IMU intrinsics and bias estimates are refined, the IMU pre-integration needs to fix the linearization points not only for \mathbf{x}_{b_k} as in (Forster et al. 2016), but for \mathbf{x}_{in} . To this end, we model the pre-integrated IMU measurements between time t_k and t_j as $\mathbf{z}_I \sim \mathcal{N}(\hat{\mathbf{z}}_I, \mathbf{Q}_I)$:

$$\mathbf{z}_I = \begin{bmatrix} \log(\Delta \mathbf{R}) \\ \Delta \mathbf{p} \\ \Delta \mathbf{v} \\ \Delta \mathbf{x}_b \end{bmatrix} = \begin{bmatrix} \log(\Delta \mathbf{R}(\mathbf{x}_{b_k}, \mathbf{x}_{in}, \mathbf{n}_\theta)) \\ \Delta \mathbf{p}(\mathbf{x}_{b_k}, \mathbf{x}_{in}, \mathbf{n}_p) \\ \Delta \mathbf{v}(\mathbf{x}_{b_k}, \mathbf{x}_{in}, \mathbf{n}_v) \\ \mathbf{n}_b \end{bmatrix} \quad (85)$$

where the accumulated noises of IMU measurements are denoted with $\mathbf{n}_I = [\mathbf{n}_\theta^\top \quad \mathbf{n}_p^\top \quad \mathbf{n}_v^\top \quad \mathbf{n}_b^\top]^\top$ and $\mathbf{n}_I \sim \mathcal{N}(\mathbf{0}, \mathbf{Q}_I)$ from Section 4.4. We linearize the above measurements at the current state estimate $\hat{\mathbf{x}}$ as:

$$\Delta \mathbf{R} = \Delta \hat{\mathbf{R}} \exp\left(\frac{\partial \delta \Delta \theta}{\partial \tilde{\mathbf{x}}_{b_k}} \tilde{\mathbf{x}}_{b_k} + \frac{\partial \delta \Delta \theta}{\partial \tilde{\mathbf{x}}_{in}} \tilde{\mathbf{x}}_{in} + \mathbf{n}_\theta\right) \quad (86)$$

$$\Delta \mathbf{p} = \Delta \hat{\mathbf{p}} + \frac{\partial \Delta \tilde{\mathbf{p}}}{\partial \tilde{\mathbf{x}}_{b_k}} \tilde{\mathbf{x}}_{b_k} + \frac{\partial \Delta \tilde{\mathbf{p}}}{\partial \tilde{\mathbf{x}}_{in}} \tilde{\mathbf{x}}_{in} + \mathbf{n}_p \quad (87)$$

$$\Delta \mathbf{v} = \Delta \hat{\mathbf{v}} + \frac{\partial \Delta \tilde{\mathbf{v}}}{\partial \tilde{\mathbf{x}}_{b_k}} \tilde{\mathbf{x}}_{b_k} + \frac{\partial \Delta \tilde{\mathbf{v}}}{\partial \tilde{\mathbf{x}}_{in}} \tilde{\mathbf{x}}_{in} + \mathbf{n}_v \quad (88)$$

Note that we would like to fix the integration of the IMU measurements with bias states and IMU intrinsics states. If we use $\hat{\mathbf{x}}^{(0)}$ denote the initial estimates while $\tilde{\mathbf{x}}^{(0)}$ denote the corresponding error states, then we have:

$$\mathbf{x} = \hat{\mathbf{x}} + \tilde{\mathbf{x}} = \hat{\mathbf{x}}^{(0)} + \tilde{\mathbf{x}}^{(0)} \quad (89)$$

$$\Rightarrow \tilde{\mathbf{x}}^{(0)} = \hat{\mathbf{x}} - \hat{\mathbf{x}}^{(0)} + \tilde{\mathbf{x}} \triangleq \Delta \hat{\mathbf{x}} + \tilde{\mathbf{x}} \quad (90)$$

The IMU measurements can be linearized with the initial estimates $\hat{\mathbf{x}}^{(0)}$ as:

$$\Delta \mathbf{R} = \Delta \hat{\mathbf{R}}^{(0)} \exp\left(\frac{\partial \delta \Delta \theta}{\partial \tilde{\mathbf{x}}_{b_k}} \tilde{\mathbf{x}}_{b_k}^{(0)} + \frac{\partial \delta \Delta \theta}{\partial \tilde{\mathbf{x}}_{in}} \tilde{\mathbf{x}}_{in}^{(0)} + \mathbf{n}_\theta\right) \quad (91)$$

$$= \mathbf{h}_R(\mathbf{x}_{I_k}, \mathbf{x}_{I_j})$$

$$\Delta \mathbf{p} = \Delta \hat{\mathbf{p}}^{(0)} + \frac{\partial \Delta \tilde{\mathbf{p}}}{\partial \tilde{\mathbf{x}}_{b_k}} \tilde{\mathbf{x}}_{b_k}^{(0)} + \frac{\partial \Delta \tilde{\mathbf{p}}}{\partial \tilde{\mathbf{x}}_{in}} \tilde{\mathbf{x}}_{in}^{(0)} + \mathbf{n}_p \quad (92)$$

$$= \mathbf{h}_p(\mathbf{x}_{I_k}, \mathbf{x}_{I_j})$$

$$\Delta \mathbf{v} = \Delta \hat{\mathbf{v}}^{(0)} + \frac{\partial \Delta \tilde{\mathbf{v}}}{\partial \tilde{\mathbf{x}}_{b_k}} \tilde{\mathbf{x}}_{b_k}^0 + \frac{\partial \Delta \tilde{\mathbf{v}}}{\partial \tilde{\mathbf{x}}_{in}} \tilde{\mathbf{x}}_{in}^0 + \mathbf{n}_v \quad (93)$$

$$= \mathbf{h}_v(\mathbf{x}_{I_k}, \mathbf{x}_{I_j})$$

The pre-integrated IMU measurement with initial biases and IMU intrinsic estimates can be rewritten as:

$$\Delta \hat{\mathbf{R}}^{(0)} = \mathbf{h}_R(\mathbf{x}_{I_k}, \mathbf{x}_{I_j}) \quad (94)$$

$$\times \exp\left(-\frac{\partial \delta \Delta \theta}{\partial \tilde{\mathbf{x}}_{b_k}} (\Delta \tilde{\mathbf{x}}_{b_k} + \tilde{\mathbf{x}}_{b_k}) - \frac{\partial \delta \Delta \theta}{\partial \tilde{\mathbf{x}}_{in}} (\Delta \tilde{\mathbf{x}}_{in} + \tilde{\mathbf{x}}_{in}) - \mathbf{n}_\theta\right)$$

$$\Delta \hat{\mathbf{p}}^{(0)} = \mathbf{h}_p(\mathbf{x}_{I_k}, \mathbf{x}_{I_j}) - \frac{\partial \Delta \tilde{\mathbf{p}}}{\partial \tilde{\mathbf{x}}_{b_k}} (\Delta \tilde{\mathbf{x}}_{b_k} + \tilde{\mathbf{x}}_{b_k})$$

$$- \frac{\partial \Delta \tilde{\mathbf{p}}}{\partial \tilde{\mathbf{x}}_{in}} (\Delta \tilde{\mathbf{x}}_{in} + \tilde{\mathbf{x}}_{in}) - \mathbf{n}_p \quad (95)$$

$$\Delta \hat{\mathbf{v}}^{(0)} = \mathbf{h}_v(\mathbf{x}_{I_k}, \mathbf{x}_{I_j}) - \frac{\partial \Delta \tilde{\mathbf{v}}}{\partial \tilde{\mathbf{x}}_{b_k}} (\Delta \tilde{\mathbf{x}}_{b_k} + \tilde{\mathbf{x}}_{b_k})$$

$$-\frac{\partial \Delta \tilde{\mathbf{v}}}{\partial \tilde{\mathbf{x}}_{in}}(\Delta \hat{\mathbf{x}}_{in} + \tilde{\mathbf{x}}_{in}) - \mathbf{n}_v \quad (96)$$

We define $\boldsymbol{\theta}_{corr}$, \mathbf{p}_{corr} and \mathbf{v}_{corr} as the orientation, position and velocity correction terms due to the linearization point changes of \mathbf{x}_{b_k} and \mathbf{x}_{in} :

$$\boldsymbol{\theta}_{corr} = \frac{\partial \delta \Delta \boldsymbol{\theta}}{\partial \tilde{\mathbf{x}}_{b_k}} \Delta \hat{\mathbf{x}}_{b_k} + \frac{\partial \delta \Delta \boldsymbol{\theta}}{\partial \tilde{\mathbf{x}}_{in}} \Delta \hat{\mathbf{x}}_{in} \quad (97)$$

$$\mathbf{p}_{corr} \triangleq \frac{\partial \Delta \tilde{\mathbf{p}}}{\partial \tilde{\mathbf{x}}_{b_k}} \Delta \hat{\mathbf{x}}_{b_k} + \frac{\partial \Delta \tilde{\mathbf{p}}}{\partial \tilde{\mathbf{x}}_{in}} \Delta \hat{\mathbf{x}}_{in} \quad (98)$$

$$\mathbf{v}_{corr} \triangleq \frac{\partial \Delta \tilde{\mathbf{v}}}{\partial \tilde{\mathbf{x}}_{b_k}} \Delta \hat{\mathbf{x}}_{b_k} + \frac{\partial \Delta \tilde{\mathbf{v}}}{\partial \tilde{\mathbf{x}}_{in}} \Delta \hat{\mathbf{x}}_{in} \quad (99)$$

Finally, the base IMU preintegration measurements are formulated as:

$$\underbrace{\begin{bmatrix} \log(\Delta \hat{\mathbf{R}}^{(0)}) \\ \Delta \hat{\mathbf{p}}^{(0)} \\ \Delta \hat{\mathbf{v}}^{(0)} \\ \mathbf{0}_{6 \times 1} \end{bmatrix}}_{\mathbf{z}'_I} = \underbrace{\begin{bmatrix} \log(\mathbf{h}_R(\mathbf{x}_{I_k}, \mathbf{x}_{I_j}) \exp(-\frac{\partial \delta \Delta \boldsymbol{\theta}}{\partial \tilde{\mathbf{x}}_{b_k}} \tilde{\mathbf{x}}_{b_k} - \frac{\partial \delta \Delta \boldsymbol{\theta}}{\partial \tilde{\mathbf{x}}_{in}} \tilde{\mathbf{x}}_{in} - \boldsymbol{\theta}_{corr}) \exp(-\mathbf{n}'_\theta)) \\ \mathbf{h}_p(\mathbf{x}_{I_k}, \mathbf{x}_{I_j}) - \frac{\partial \Delta \tilde{\mathbf{p}}}{\partial \tilde{\mathbf{x}}_{b_k}} \tilde{\mathbf{x}}_{b_k} - \frac{\partial \Delta \tilde{\mathbf{p}}}{\partial \tilde{\mathbf{x}}_{in}} \tilde{\mathbf{x}}_{in} - \mathbf{p}_{corr} - \mathbf{n}_p \\ \mathbf{h}_v(\mathbf{x}_{I_k}, \mathbf{x}_{I_j}) - \frac{\partial \Delta \tilde{\mathbf{v}}}{\partial \tilde{\mathbf{x}}_{b_k}} \tilde{\mathbf{x}}_{b_k} - \frac{\partial \Delta \tilde{\mathbf{v}}}{\partial \tilde{\mathbf{x}}_{in}} \tilde{\mathbf{x}}_{in} - \mathbf{v}_{corr} - \mathbf{n}_v \\ \mathbf{x}_{b_j} - \mathbf{x}_{b_k} - \mathbf{n}_b \end{bmatrix}}_{\mathbf{h}_I(\mathbf{x}, \mathbf{n}'_I)} \quad (100)$$

The new IMU measurement noise \mathbf{n}'_I is computed as:

$$\mathbf{n}'_I \triangleq \begin{bmatrix} \mathbf{n}'_\theta \\ \mathbf{n}_p \\ \mathbf{n}_v \\ \mathbf{n}_b \end{bmatrix} = \underbrace{\begin{bmatrix} \mathbf{J}_r(-\boldsymbol{\theta}_{corr}) & \mathbf{0}_{3 \times 12} \\ \mathbf{0}_{12 \times 3} & \mathbf{I}_{12} \end{bmatrix}}_{\mathbf{H}_{n'_I}} \begin{bmatrix} \mathbf{n}_\theta \\ \mathbf{n}_p \\ \mathbf{n}_v \\ \mathbf{n}_b \end{bmatrix} \triangleq \mathbf{H}_{n'_I} \mathbf{n}_I \quad (101)$$

with covariance $\mathbf{n}'_I \sim \mathcal{N}(\mathbf{0}, \mathbf{Q}'_I)$ and $\mathbf{Q}'_I = \mathbf{H}_{n'_I} \mathbf{Q}_I \mathbf{H}_{n'_I}^\top$. As compared to the conventional IMU pre-integration (Forster et al. 2016) with only mean correction, we have both the mean and covariance corrections when linearization point changes for biases and IMU intrinsics. Finally, the corresponding base IMU preintegration cost is:

$$\mathbb{C}_I \triangleq \|\mathbf{z}_I \ominus \mathbf{h}(\mathbf{x}_{I_k}, \mathbf{x}_{I_j}, \mathbf{x}_{in})\|_{(\mathbf{Q}'_I)^{-1}}^2 \quad (102)$$

6 Auxiliary Inertial Costs

Leveraging the base IMU preintegration measurements (100), we now derive the costs for the auxiliary IMU and gyroscope by using the rigid body constraints between the base and auxiliary IMUs.

6.1 Auxiliary IMU Cost

As the auxiliary IMUs are considered to be temporally asynchronous with the base IMU, we employ pose interpolation to associate the base IMU state with the auxiliary IMU state. The rigid body constraint between the auxiliary and base IMU with interpolation terms is given by:

$$\begin{bmatrix} {}^G \mathbf{R}_{I_a} & {}^G \mathbf{p}_{I_a} \\ \mathbf{0}_{1 \times 3} & 1 \end{bmatrix} \triangleq \begin{bmatrix} {}^G \mathbf{R}_{I_{in}} & {}^G \mathbf{p}_{I_{in}} \\ \mathbf{0}_{1 \times 3} & 1 \end{bmatrix} \begin{bmatrix} {}^I \mathbf{R} & {}^I \mathbf{p}_{I_a} \\ \mathbf{0}_{1 \times 3} & 1 \end{bmatrix} \quad (103)$$

where $\{{}^G \mathbf{R}_{I_{in}}, {}^G \mathbf{p}_{I_{in}}\}$ is the interpolation pose is computed with constant linear and angular velocity:

$$\begin{bmatrix} {}^G \mathbf{R}_{I_{in}} & {}^G \mathbf{p}_{I_{in}} \\ \mathbf{0}_{1 \times 3} & 1 \end{bmatrix} = \begin{bmatrix} {}^G \mathbf{R} & {}^G \mathbf{p}_I \\ \mathbf{0}_{1 \times 3} & 1 \end{bmatrix} \begin{bmatrix} \exp({}^I \boldsymbol{\omega} t_d) & {}^G \mathbf{v}_I t_d \\ \mathbf{0}_{1 \times 3} & 1 \end{bmatrix} \quad (104)$$

The auxiliary IMU pose $\{{}^G \mathbf{R}_{I_a}, {}^G \mathbf{p}_{I_a}\}$ can be found with the base IMU pose $\{{}^G \mathbf{R}_I, {}^G \mathbf{p}_I\}$ as:

$${}^G \mathbf{R}_{I_a} = {}^G \mathbf{R}_I \exp({}^I \boldsymbol{\omega} t_d) {}^I \mathbf{R} \quad (105)$$

$${}^G \mathbf{p}_{I_a} = {}^G \mathbf{R}_I {}^G \mathbf{v}_I t_d + {}^G \mathbf{p}_I + {}^G \mathbf{R}_I \exp({}^I \boldsymbol{\omega} t_d) {}^I \mathbf{p}_{I_a} \quad (106)$$

There is no need to keep auxiliary IMU pose in the state vector, because the auxiliary IMU pose can be expressed by the base IMU state \mathbf{x}_I and extrinsics \mathbf{x}_{I_a} . The auxiliary IMU state (21) only contains the auxiliary IMU velocity and biases. We need to reformulate the preintegration (41)-(43) for the auxiliary IMU cost with the rigid body constraints (105)-(106). Following Eq. (100), with some abuse of the notations for the auxiliary IMU pre-integrated measurements \mathbf{z}'_{I_a} and noises \mathbf{n}'_{I_a} , we have:

$$\underbrace{\begin{bmatrix} \log(\Delta \hat{\mathbf{R}}^{(0)}) \\ \Delta \hat{\mathbf{p}}^{(0)} \\ \Delta \hat{\mathbf{v}}^{(0)} \\ \mathbf{0}_{6 \times 1} \end{bmatrix}}_{\mathbf{z}'_{I_a}} = \underbrace{\begin{bmatrix} \log(\mathbf{h}_R(\cdot) \exp(-\frac{\partial \delta \Delta \boldsymbol{\theta}}{\partial \tilde{\mathbf{x}}_{b_k}} \tilde{\mathbf{x}}_{b_k} - \frac{\partial \delta \Delta \boldsymbol{\theta}}{\partial \tilde{\mathbf{x}}_{in}} \tilde{\mathbf{x}}_{in} - \boldsymbol{\theta}_{A_{corr}}) \exp(-\mathbf{n}'_\theta)) \\ \mathbf{h}_p(\cdot) - \frac{\partial \Delta \tilde{\mathbf{p}}}{\partial \tilde{\mathbf{x}}_{b_k}} \tilde{\mathbf{x}}_{b_k} - \frac{\partial \Delta \tilde{\mathbf{p}}}{\partial \tilde{\mathbf{x}}_{in}} \tilde{\mathbf{x}}_{in} - \mathbf{p}_{A_{corr}} - \mathbf{n}_p \\ \mathbf{h}_v(\cdot) - \frac{\partial \Delta \tilde{\mathbf{v}}}{\partial \tilde{\mathbf{x}}_{b_k}} \tilde{\mathbf{x}}_{b_k} - \frac{\partial \Delta \tilde{\mathbf{v}}}{\partial \tilde{\mathbf{x}}_{in}} \tilde{\mathbf{x}}_{in} - \mathbf{v}_{A_{corr}} - \mathbf{n}_v \\ \mathbf{x}_{A_{b_j}} - \mathbf{x}_{A_{b_k}} - \mathbf{n}_b \end{bmatrix}}_{\mathbf{h}_A(\mathbf{x}, \mathbf{n}'_{I_a})} \quad (107)$$

where we have defined $\mathbf{h}_R(\cdot)$, $\mathbf{h}_p(\cdot)$ and $\mathbf{h}_v(\cdot)$ for the auxiliary IMU:

$$\begin{aligned} \mathbf{h}_R(\cdot) &\triangleq {}^G \mathbf{R}_{I_{ak}}^\top {}^G \mathbf{R}_{I_{aj}} \\ &\triangleq ({}^G \mathbf{R}_I \exp({}^I \boldsymbol{\omega} t_d) {}^I \mathbf{R})^\top {}^G \mathbf{R}_I \exp({}^I \boldsymbol{\omega} t_d) {}^I \mathbf{R} \\ &\triangleq \mathbf{h}_R(\mathbf{x}_{I_k}, \mathbf{x}_{I_j}, \mathbf{x}_{I_a}) \end{aligned} \quad (108)$$

$$\begin{aligned} \mathbf{h}_p(\cdot) &\triangleq {}^G \mathbf{R}_{I_{ak}}^\top \left({}^G \mathbf{p}_{I_{aj}} - {}^G \mathbf{p}_{I_{ak}} - {}^G \mathbf{v}_{I_{ak}} \delta t - \frac{1}{2} {}^G \mathbf{g} \delta t^2 \right) \\ &\triangleq \mathbf{h}_p(\mathbf{x}_{I_k}, \mathbf{x}_{I_j}, \mathbf{x}_{I_{ak}}, \mathbf{x}_{I_a}) \end{aligned} \quad (109)$$

$$\begin{aligned} \mathbf{h}_v(\cdot) &\triangleq {}^G \mathbf{R}_{I_{ak}}^\top ({}^G \mathbf{v}_{I_{aj}} - {}^G \mathbf{v}_{I_{ak}} + {}^G \mathbf{g} \delta t) \\ &\triangleq \mathbf{h}_v(\mathbf{x}_{I_k}, \mathbf{x}_{I_{ak}}, \mathbf{x}_{I_{aj}}, \mathbf{x}_{I_a}) \end{aligned} \quad (110)$$

Following Eq. (97)-(99), the linearization correction terms of orientation $\boldsymbol{\theta}_{A_{corr}}$, position $\mathbf{p}_{A_{corr}}$ and velocity $\mathbf{v}_{A_{corr}}$ for the auxiliary IMU are given by:

$$\boldsymbol{\theta}_{A_{corr}} = \frac{\partial \delta \Delta \boldsymbol{\theta}}{\partial \tilde{\mathbf{x}}_{A_{b_k}}} \Delta \hat{\mathbf{x}}_{A_{b_k}} + \frac{\partial \delta \Delta \boldsymbol{\theta}}{\partial \tilde{\mathbf{x}}_{A_{in}}} \Delta \hat{\mathbf{x}}_{A_{in}} \quad (111)$$

$$\mathbf{p}_{A_{corr}} = \frac{\partial \Delta \tilde{\mathbf{p}}}{\partial \tilde{\mathbf{x}}_{A_{b_k}}} \Delta \hat{\mathbf{x}}_{A_{b_k}} + \frac{\partial \Delta \tilde{\mathbf{p}}}{\partial \tilde{\mathbf{x}}_{A_{in}}} \Delta \hat{\mathbf{x}}_{A_{in}} \quad (112)$$

$$\mathbf{v}_{A_{corr}} = \frac{\partial \Delta \tilde{\mathbf{v}}}{\partial \tilde{\mathbf{x}}_{A_{b_k}}} \Delta \hat{\mathbf{x}}_{A_{b_k}} + \frac{\partial \Delta \tilde{\mathbf{v}}}{\partial \tilde{\mathbf{x}}_{A_{in}}} \Delta \hat{\mathbf{x}}_{A_{in}} \quad (113)$$

Finally, the corresponding auxiliary IMU cost is given by:

$$\mathbb{C}_{I_a} \triangleq \|\mathbf{z}_{I_a} \ominus \mathbf{h}(\mathbf{x}, \mathbf{n}'_{I_a})\|_{(\mathbf{Q}'_{I_a})^{-1}}^2 \quad (114)$$

6.2 Auxiliary Gyroscope Cost

Similarly, the auxiliary gyroscope cost can be derived. Note that we only integrate the angular velocity and gyro biases and the gyroscope state is defined as gyroscope biases and the \mathbf{x}_{G_w} . The rotation constraints is written as:

$${}^G_{I_g}\mathbf{R} = {}^G_I\mathbf{R} \exp({}^I\boldsymbol{\omega} t_{I_g}) {}^I_{I_g}\mathbf{R} \quad (115)$$

Reusing the notation, $\mathbf{h}_R(\cdot)$ is written for the auxiliary IMU as [see Eq. (41)]:

$$\begin{aligned} \mathbf{h}_R(\cdot) &\triangleq {}^G_{I_g}\mathbf{R} {}^{\top G}_{I_g} \mathbf{R} \\ &\triangleq \left({}^G_I\mathbf{R} \exp({}^I_k\boldsymbol{\omega} t_{I_g}) {}^I_{I_g}\mathbf{R} \right) {}^{\top G}_{I_g} \mathbf{R} \exp({}^I_j\boldsymbol{\omega} t_{I_g}) {}^I_{I_g}\mathbf{R} \\ &\triangleq \mathbf{h}_R(\mathbf{x}_{I_k}, \mathbf{x}_{I_j}, \mathbf{x}_{I_g}) \end{aligned} \quad (116)$$

The pre-integrated auxiliary gyroscope measurements and noises is found as:

$$\begin{aligned} \underbrace{\begin{bmatrix} \log(\Delta \hat{\mathbf{R}}^{(0)}) \\ \mathbf{0}_{3 \times 1} \end{bmatrix}}_{\mathbf{z}_{I_g}} &= \underbrace{\begin{bmatrix} \log \left(\mathbf{h}_R(\cdot) \exp \left(-\frac{\partial \delta \Delta \boldsymbol{\theta}}{\partial \mathbf{b}_{G_{gk}}} \tilde{\mathbf{b}}_{G_{gk}} - \frac{\partial \delta \Delta \boldsymbol{\theta}}{\partial \tilde{\mathbf{x}}_{G_{in}}} \tilde{\mathbf{x}}_{G_{in}} - \boldsymbol{\theta}_{G_{corr}} \right) \exp(-\mathbf{n}'_g) \right) \\ \mathbf{b}_{G_{gj}} - \mathbf{b}_{G_{gk}} - \mathbf{n}_g \end{bmatrix}}_{\mathbf{h}(\mathbf{x}, \mathbf{n}'_{I_g})} \end{aligned} \quad (117)$$

where the linearization correction terms:

$$\boldsymbol{\theta}_{G_{corr}} = \frac{\partial \delta \Delta \boldsymbol{\theta}}{\partial \tilde{\mathbf{b}}_{G_{gk}}} \Delta \hat{\mathbf{b}}_{G_{gk}} + \frac{\partial \delta \Delta \boldsymbol{\theta}}{\partial \tilde{\mathbf{x}}_{G_{in}}} \Delta \hat{\mathbf{x}}_{G_{in}} \quad (118)$$

Finally, the auxiliary gyroscope cost is given by:

$$\mathbb{C}_{I_g} \triangleq \left\| \mathbf{z}_{I_g} \ominus \mathbf{h}(\mathbf{x}, \mathbf{n}'_{I_g}) \right\|_{(\mathbf{Q}'_{I_g})^{-1}}^2 \quad (119)$$

6.3 Auxiliary Inertial Sensor Initialization

We now initialize the IMU state \mathbf{x}_{I_a} , which contains the velocity ${}^G\mathbf{v}_{I_a}$ and biases (\mathbf{b}_{A_g} and \mathbf{b}_{A_a}) of the auxiliary IMU, as follows:

- The initial velocity of the auxiliary IMU is computed based on the rigid body constraints:

$${}^G\mathbf{v}_{I_a} = {}^G\mathbf{v}_I + {}^G_I\mathbf{R} [{}^I_{I_a}\mathbf{R} {}^I_{I_a}\boldsymbol{\omega}] {}^I_{I_a}\mathbf{p}_{I_a} \quad (120)$$

- For $\hat{\mathbf{b}}_{A_{gk}}$, we integrate the angular velocity measurements with zero bias and then solve the following linear system:

$$\frac{\partial \Delta \tilde{\mathbf{v}}}{\partial \tilde{\mathbf{b}}_{A_{gk}}} \cdot \hat{\mathbf{b}}_{A_{gk}} = \log \left(\Delta \mathbf{R} {}^{\top G}_{I_{ak}} \mathbf{R} {}^{\top G}_{I_{ak+1}} \mathbf{R} \right) \quad (121)$$

where $\log(\cdot)$ denotes the log operation of $\mathcal{SO}(3)$ (Barfoot 2017).

- For $\hat{\mathbf{b}}_{A_{ak}}$, the accelerometer bias is initialized with $\mathbf{0}_{3 \times 1}$.

7 Visual Costs

We build the complete camera measurement function $\mathbf{h}_C(\cdot)$ by incorporating the distortion function $\mathbf{h}_d(\cdot)$ [see Eq. (7)], the projection function $\mathbf{h}_p(\cdot)$ [see Eq. (11)] and the transformation function $\mathbf{h}_t(\cdot)$ [see Eq. (12)]:

$$\mathbf{z}_C = \mathbf{h}_C(\mathbf{x}) + \mathbf{n}_C \quad (122)$$

$$= \mathbf{h}_d(\mathbf{z}_n, \mathbf{x}_{C_{in}}) + \mathbf{n}_C \quad (123)$$

$$= \mathbf{h}_d(\mathbf{h}_p({}^C_k\mathbf{p}_f), \mathbf{x}_{C_{in}}) + \mathbf{n}_C \quad (124)$$

$$= \mathbf{h}_d(\mathbf{h}_p(\mathbf{h}_t({}^G_{C(t)}\mathbf{R}, {}^G\mathbf{p}_{C(t)}, {}^G\mathbf{p}_f)), \mathbf{x}_{C_{in}}) + \mathbf{n}_C \quad (125)$$

We need to linearize the camera model for update, which is given by:

$$\tilde{\mathbf{z}}_C \simeq \mathbf{H}_C \tilde{\mathbf{x}} + \mathbf{n}_C \quad (126)$$

where $\tilde{\mathbf{z}}_C \triangleq \mathbf{z}_C - \mathbf{h}_C(\hat{\mathbf{x}})$ and $\mathbf{H}_C \triangleq \frac{\partial \tilde{\mathbf{z}}_C}{\partial \tilde{\mathbf{x}}}$. Using the chainrule we get the following Jacobian matrix:

$$\begin{aligned} \mathbf{H}_C &= \begin{bmatrix} \frac{\partial \tilde{\mathbf{z}}_C}{\partial \tilde{\mathbf{x}}_I} & \frac{\partial \tilde{\mathbf{z}}_C}{\partial \tilde{\mathbf{x}}_{I_C}} & \frac{\partial \tilde{\mathbf{z}}_C}{\partial \tilde{\mathbf{x}}_{C_{in}}} & \frac{\partial \tilde{\mathbf{z}}_C}{\partial \tilde{\mathbf{x}}_f} \end{bmatrix} \\ &= \begin{bmatrix} \mathbf{H}_{\mathbf{p}_f} \frac{\partial {}^C\tilde{\mathbf{p}}_f}{\partial \tilde{\mathbf{x}}_I} & \mathbf{H}_{\mathbf{p}_f} \frac{\partial {}^C\tilde{\mathbf{p}}_f}{\partial \tilde{\mathbf{x}}_{I_C}} & \frac{\partial \tilde{\mathbf{z}}_C}{\partial \tilde{\mathbf{x}}_{C_{in}}} & \mathbf{H}_{\mathbf{p}_f} \frac{\partial {}^C\tilde{\mathbf{p}}_f}{\partial \tilde{\mathbf{x}}_f} \end{bmatrix} \end{aligned} \quad (127)$$

where $\mathbf{H}_{\mathbf{p}_f} = \frac{\partial \tilde{\mathbf{z}}_C}{\partial \tilde{\mathbf{z}}_n} \frac{\partial \tilde{\mathbf{z}}_n}{\partial {}^C\tilde{\mathbf{p}}_f}$. All the pertinent matrices $\frac{\partial {}^C\tilde{\mathbf{p}}_f}{\partial \tilde{\mathbf{x}}_I}$, $\frac{\partial {}^C\tilde{\mathbf{p}}_f}{\partial \tilde{\mathbf{x}}_{I_C}}$, $\frac{\partial {}^C\tilde{\mathbf{p}}_f}{\partial \tilde{\mathbf{x}}_f}$ and $\mathbf{H}_{\mathbf{p}_f}$ are computed as shown in (Yang et al. 2023a). Hence, the visual cost can be formulated:

$$\mathbb{C}_C \triangleq \|\mathbf{z}_C - \mathbf{h}_C(\mathbf{x})\|_{\mathbf{Q}_C^{-1}}^2 \quad (128)$$

Note that in our implementation, we use pose interpolation to model the time offset and RS calibration (Yang et al. 2023a). For example, if the feature measurement is in the m -th row with total M rows in an image, we can find two bounding poses k and $k+1$ based on the measurement time t . The corresponding time t is between two IMU poses, $t_k \leq t \leq t_{k+1}$. We can then find the *virtual* IMU pose $\{{}^G_{I(t)}\mathbf{R}, {}^G\mathbf{p}_{I(t)}\}$ between poses at k and $k+1$:

$$\lambda = (t_I + t_d + \frac{m}{M}t_r - t_k) / (t_{k+1} - t_k) \quad (129)$$

$${}^G_{I(t)}\mathbf{R} = {}^G_{I_k}\mathbf{R} \exp \left(\lambda \log \left({}^G_{I_k}\mathbf{R} {}^{\top G}_{I_{k+1}}\mathbf{R} \right) \right) \quad (130)$$

$${}^G\mathbf{p}_{I(t)} = (1 - \lambda) {}^G\mathbf{p}_{I_k} + \lambda {}^G\mathbf{p}_{I_{k+1}} \quad (131)$$

8 Observability Analysis

Observability analysis plays an important role in state estimation for VINS (Huang 2012; Martinelli 2013). This analysis allows for determining the minimum measurements needed to determine the state and identify degenerate motions which may degrade system performance by introducing additional unobservable directions for certain parameters (Yang et al. 2019; Wu et al. 2017; Lee et al. 2020; Yang et al. 2020b). Since MVIS is becoming popular, an observability analysis for such a system with full calibration parameters, especially IMU-IMU spatial-temporal calibration, is needed to better understand the underlying system property.

8.1 Reduced State Vector

Although the proposed MVIS supports arbitrary number of auxiliary inertial sensors and cameras, for simplicity and without loss of generality, we use a typical system consisting of only one base IMU, one auxiliary IMU, one auxiliary gyroscope and one RS camera as unique sensors for the following observability analysis (Hesch et al. 2014; Yang and Huang 2019; Yang et al. 2023b).

To simplify the ensuing derivation, we re-order the state vector and assume that the base IMU, auxiliary inertial sensors are all kept as full states (i.e. including the full auxiliary inertial state). All the states will be propagated forward with regarding to time. The rigid body constraints and visual measurements will be used to update these states. Specifically, the state vector includes all the necessary parameters for the observability analysis as:

$$\mathbf{x} = [\mathbf{x}_B^\top \quad \mathbf{x}_A^\top \quad \mathbf{x}_G^\top \quad \mathbf{x}_{calib}^\top \quad G\mathbf{p}_f^\top]^\top \quad (132)$$

$$\triangleq [\mathbf{x}_I^\top \quad \mathbf{x}_{in}^\top \quad \mathbf{x}_{I_a}^\top \quad \mathbf{x}_{A_{in}}^\top \quad \mathbf{x}_{I_g}^\top \quad \mathbf{x}_{G_{in}}^\top \quad \mathbf{x}_{Ex}^\top \quad \mathbf{x}_{C_{in}}^\top \quad G\mathbf{p}_f^\top]^\top \quad (133)$$

Note that the auxiliary IMU and gyroscope states are:

$$\mathbf{x}_{I_a} = [I_a \bar{q}^\top \quad G\mathbf{p}_{I_a}^\top \quad G\mathbf{v}_{I_a}^\top \quad \mathbf{b}_{A_g}^\top \quad \mathbf{b}_{A_a}^\top]^\top \quad (134)$$

$$\mathbf{x}_{I_g} = [I_g \bar{q}^\top \quad \mathbf{b}_{G_g}^\top]^\top \quad (135)$$

After propagation, the visual measurements and rigid body constraints between inertial sensors are used to update the states with:

$$\mathbf{z} = [\mathbf{z}_C^\top \quad \mathbf{z}_A^\top \quad \mathbf{z}_G^\top]^\top \quad (136)$$

where \mathbf{z}_C denotes the visual cost, \mathbf{z}_A and \mathbf{z}_G represent the rigid body pose constraints between auxiliary and base inertial sensors:

$$\mathbf{z}_A = \begin{bmatrix} \log(G\mathbf{R}_a^\top G\mathbf{R}_I^I \mathbf{R}) \\ G\mathbf{p}_{I_a} - G\mathbf{p}_I - G\mathbf{R}_I^I \mathbf{p}_{I_a} \end{bmatrix} \quad (137)$$

$$\mathbf{z}_G = \log(G\mathbf{R}_g^\top G\mathbf{R}_I^I \mathbf{R}) \quad (138)$$

8.2 Linearized Observability Analysis

The overall state transition matrix can be written as:

$$\Phi = \text{Diag}\{\Phi_B, \Phi_A, \Phi_G, \Phi_{calib}, \Phi_F\} \quad (139)$$

The detailed derivations for Φ_B , Φ_A , Φ_G , Φ_{calib} and Φ_F can be found in Appendix C. The corresponding linearization Jacobians for Eq. (136) can be listed as:

$$\frac{\partial \tilde{\mathbf{z}}}{\partial \tilde{\mathbf{x}}} = \begin{bmatrix} \frac{\partial \tilde{\mathbf{z}}_C}{\partial \tilde{\mathbf{x}}} \\ \frac{\partial \tilde{\mathbf{z}}_A}{\partial \tilde{\mathbf{x}}} \\ \frac{\partial \tilde{\mathbf{z}}_G}{\partial \tilde{\mathbf{x}}} \end{bmatrix} = \begin{bmatrix} \mathbf{H}_{CB} & \mathbf{0} & \mathbf{0} & \mathbf{H}_{CC} & \mathbf{H}_{CF} \\ \mathbf{H}_{AB} & \mathbf{H}_{AA} & \mathbf{0} & \mathbf{H}_{AC} & \mathbf{0} \\ \mathbf{H}_{GB} & \mathbf{0} & \mathbf{H}_{GG} & \mathbf{H}_{GC} & \mathbf{0} \end{bmatrix} \quad (140)$$

where \mathbf{H}_{ZX} denotes the Jacobians of measurement Z regarding to state parameter X , which can be referred to Appendix D. The observability matrix can be written as:

$$\begin{aligned} \mathbf{M} &= \begin{bmatrix} \frac{\partial \tilde{\mathbf{z}}_C}{\partial \tilde{\mathbf{x}}} \\ \frac{\partial \tilde{\mathbf{z}}_A}{\partial \tilde{\mathbf{x}}} \\ \frac{\partial \tilde{\mathbf{z}}_G}{\partial \tilde{\mathbf{x}}} \end{bmatrix} \Phi = \begin{bmatrix} \mathbf{M}_{CB} & \mathbf{0} & \mathbf{0} & \mathbf{M}_{CC} & \mathbf{M}_{CF} \\ \mathbf{M}_{AB} & \mathbf{M}_{AA} & \mathbf{0} & \mathbf{M}_{AC} & \mathbf{0} \\ \mathbf{M}_{GB} & \mathbf{0} & \mathbf{M}_{GG} & \mathbf{M}_{GC} & \mathbf{0} \end{bmatrix} \\ &= \begin{bmatrix} \mathbf{H}_{CB}\Phi_B & \mathbf{0} & \mathbf{0} & \mathbf{H}_{CC}\Phi_C & \mathbf{H}_{CF}\Phi_F \\ \mathbf{H}_{AB}\Phi_B & \mathbf{H}_{AA}\Phi_A & \mathbf{0} & \mathbf{H}_{AC}\Phi_C & \mathbf{0} \\ \mathbf{H}_{GB}\Phi_B & \mathbf{0} & \mathbf{H}_{GG}\Phi_G & \mathbf{H}_{GC}\Phi_C & \mathbf{0} \end{bmatrix} \end{aligned} \quad (141)$$

Table 2. Degenerate motions for auxiliary IMU and gyroscope.

Motion Types	Auxiliary IMU	Auxiliary Gyroscope
No Rotation	I_{I_a}	$I_{I_g} \mathbf{R}$ and t_{dg}
One-axis Rotation	I_{I_a} along rotation axis	$I_{I_g} \mathbf{R}$ along rotation axis
Constant I_{I_a}	I_{I_a} along rotation axis	$I_{I_g} \mathbf{R}$ along rotation axis, t_{dg}
Constant I_{I_a} , constant $G\mathbf{v}_I$	I_{I_a} along rotation axis, t_{da}	$I_{I_g} \mathbf{R}$ along rotation axis, t_{dg}
Constant I_{I_a} , constant I_{I_g}	I_{I_a} along rotation axis	$I_{I_g} \mathbf{R}$ along rotation axis, t_{dg}

By closely inspecting the observability matrix, we have the following Lemma:

Lemma 1. *The proposed MVIS has four unobservable directions corresponding to the global yaw rotation and the global translation:*

$$\mathbf{N} = \begin{bmatrix} I_0 \mathbf{R}^G \mathbf{g} & \mathbf{0}_3 \\ G\mathbf{p}_{I_0}^G \mathbf{g} & \mathbf{I}_3 \\ G\mathbf{v}_{I_0}^G \mathbf{g} & \mathbf{0}_3 \\ \mathbf{0}_{27 \times 1} & \mathbf{0}_{27 \times 3} \\ I_{a0} \mathbf{R}^G \mathbf{g} & \mathbf{0}_3 \\ G\mathbf{p}_{I_{a0}}^G \mathbf{g} & \mathbf{I}_3 \\ G\mathbf{v}_{I_{a0}}^G \mathbf{g} & \mathbf{0}_3 \\ \mathbf{0}_{27 \times 1} & \mathbf{0}_{27 \times 3} \\ I_{g0} \mathbf{R}^G \mathbf{g} & \mathbf{0}_3 \\ \mathbf{0}_{36 \times 1} & \mathbf{0}_{36 \times 3} \\ G\mathbf{p}_f^G \mathbf{g} & \mathbf{I}_3 \end{bmatrix} \quad (142)$$

These four unobservable directions are similar to the 4 classical unobservable directions for a mono VINS system (Hesch et al. 2014). From this lemma, we can conclude that the system will not lose unobservable directions by simply adding more inertial sensors (IMU or gyroscopes). It should also be pointed out that the velocity of IMU state will become unobservable if no visual measurements to static landmarks are available. Hence, without cameras, naively adding auxiliary IMUs will not significantly improve the system localization accuracy due to lack of global constraints to the base IMU velocity. It can be observed that the calibration parameters, including \mathbf{x}_{in} , $\mathbf{x}_{A_{in}}$, $\mathbf{x}_{G_{in}}$ and \mathbf{x}_{Ex} , are highly related to the sensor motion. Under fully excited motions, these parameters are observable, which can be seen from our simulation results in Section 10.1.

9 Degenerate Motion Analysis

While the degenerate motions for the IMU-camera spatial-temporal parameters, IMU intrinsics and camera intrinsics have been studied (Yang et al. 2019, 2020b, 2023b), in this paper, we for the first time study the degenerate motions for the IMU-IMU spatial-temporal calibration of MVIS.

9.1 Spatial-Temporal Calibration of Auxiliary Inertial Sensors

In particular, we have identified the degenerate motions for the spatial-temporal calibration between the auxiliary inertial sensors and the base IMU, as summarized in Table 2, which will be explained in detail below.

9.1.1 No Rotation If the MVIS undergoes 3D motion but without rotation, the translation I_{I_a} between the auxiliary and base IMUs, the rotation $I_{I_g} \mathbf{R}$ and time offset between the auxiliary gyroscope and the base IMU, will be unobservable.

The unobservable directions \mathbf{N}_{NR} are given by:

$$\mathbf{N}_{NR} = \begin{bmatrix} \mathbf{0}_{39 \times 3} & \mathbf{0}_{39 \times 3} & \mathbf{0}_{39 \times 1} \\ \mathbf{I}_3 & \mathbf{0}_3 & \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{30 \times 3} & \mathbf{0}_{30 \times 3} & \mathbf{0}_{30 \times 1} \\ \mathbf{0}_3 & \mathbf{I}_3 & \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{12 \times 3} & \mathbf{0}_{12 \times 3} & \mathbf{0}_{12 \times 1} \\ \mathbf{I}_0^G \mathbf{R} & \mathbf{0}_3 & \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{1 \times 3} & \mathbf{0}_{1 \times 3} & 0 \\ \mathbf{0}_3 & \mathbf{I}_3 & \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{1 \times 3} & \mathbf{0}_{1 \times 3} & 1 \\ \mathbf{0}_{19 \times 3} & \mathbf{0}_{19 \times 3} & \mathbf{0}_{19 \times 1} \end{bmatrix} \quad (143)$$

9.1.2 One-Axis Rotation If the system undergoes 3D motion but with only one-axis rotation (which is common for micro aerial vehicles), the translation ${}^I \mathbf{p}_{I_a}$ between the auxiliary and base IMUs, the rotation ${}^I_g \mathbf{R}$ between the auxiliary gyroscope and the base IMU will be unobservable, along with the rotation axis \mathbf{k} , which is given by:

$$\mathbf{N}_{OA} = \begin{bmatrix} \mathbf{0}_{39 \times 1} & \mathbf{0}_{39 \times 1} \\ \mathbf{I}_0^G \mathbf{R} \mathbf{I}_0 \mathbf{k} & \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{30 \times 1} & \mathbf{0}_{30 \times 1} \\ \mathbf{0}_{3 \times 1} & \mathbf{I}_{g0} \mathbf{k} \\ \mathbf{0}_{12 \times 1} & \mathbf{0}_{12 \times 1} \\ \mathbf{I}_0 \mathbf{k} & \mathbf{0}_{3 \times 1} \\ 0 & 0 \\ \mathbf{0}_{3 \times 1} & \mathbf{I}_{g0} \mathbf{k} \\ \mathbf{0}_{19 \times 1} & \mathbf{0}_{19 \times 1} \end{bmatrix} \quad (144)$$

Note that we, for the first time, explicitly found that one-axis rotation will cause the rotation calibration between the auxiliary gyroscope and base IMU to become unobservable. We verify this finding with simulations in Section 10.2.

9.1.3 Constant Local Angular Velocity If the MVIS undergoes constant local angular velocity with random 3D translation for the base IMU, the translation ${}^I \mathbf{p}_{I_a}$ between the base and auxiliary IMUs is still unobservable along the rotation axis. In addition, the rotation ${}^I_a \mathbf{R}$ and the time offset t_{I_g} between the base IMU and the auxiliary gyroscope are also unobservable.

9.1.4 Constant Local Angular and Global Linear Velocity If the MVIS undergoes constant ${}^I \boldsymbol{\omega}$ and constant ${}^G \mathbf{v}_I$ for base IMU, the translation and time offset between the base and auxiliary IMUs, the rotation and time offset between the base IMU and the auxiliary gyroscope are not observable.

9.1.5 Constant Local Angular and Linear Velocity When the ${}^I \boldsymbol{\omega}$ and ${}^I \mathbf{v}$ are constant for the base IMU, the time offset t_d between the base IMU and the cameras, as well as the time offset t_{d_g} between the base IMU and the gyroscope are both unobservable. However, the time offset t_{d_a} between the base and auxiliary IMUs is still observable (see Fig. 6), which actually counters our intuitions. This is due to the fact that the local constant velocity assumption will be invalid for the auxiliary IMU if the base IMU is undergoing constant local linear and angular velocity. The local angular velocity and acceleration of the auxiliary IMU can be represented as:

$${}^I_a \boldsymbol{\omega} = {}^I_a \mathbf{R} {}^I \boldsymbol{\omega} \quad (145)$$

$${}^I_a \mathbf{a} = {}^I_a \mathbf{R} ({}^I \mathbf{a} + [{}^I \boldsymbol{\alpha}] {}^I \mathbf{p}_{I_a} + [{}^I \boldsymbol{\omega}] [{}^I \boldsymbol{\omega}] {}^I \mathbf{p}_{I_a}) \quad (146)$$

Table 3. Summary of basic degenerate motions for auxiliary inertial intrinsic calibration. Any combinations of these unit motion primitives are degenerate. Note that d_{A*} is column-wise element from \mathbf{D}_{A*} , with d_{Gw} is column-wise element from \mathbf{D}_{G*} . $t_{A_{gi}}$, $i = 1 \dots 9$ are the elements from \mathbf{T}_{A_g} for g-sensitivity.

Motion Types	Nullspace Dim.	Unobservable Parameters
constant ${}^A_w \omega_1$	1	$d_{A_{w1}}$
constant ${}^A_w \omega_2$	2	$d_{A_{w2}}, d_{A_{w3}}$
constant ${}^A_w \omega_3$	3	$d_{A_{w4}}, d_{A_{w5}}, d_{A_{w6}}$
constant ${}^A_a a_1$	3	$d_{A_{a1}}$, pitch and yaw of ${}^I_a \mathbf{R}$
constant ${}^A_a a_2$	3	$d_{A_{a2}}, d_{A_{a3}}$, roll of ${}^I_a \mathbf{R}$
constant ${}^A_a a_3$	3	$d_{A_{a4}}, d_{A_{a5}}, d_{A_{a6}}$
constant ${}^I_a a_1$	1	$t_{A_{g1}}, t_{A_{g2}}, t_{A_{g3}}$
constant ${}^I_a a_2$	2	$t_{A_{g4}}, t_{A_{g5}}, t_{A_{g6}}$
constant ${}^I_a a_3$	3	$t_{A_{g7}}, t_{A_{g8}}, t_{A_{g9}}$
constant ${}^G_w \omega_1$	1	$d_{G_{w1}}$
constant ${}^G_w \omega_2$	2	$d_{G_{w2}}, d_{G_{w3}}$
constant ${}^G_w \omega_3$	3	$d_{G_{w4}}, d_{G_{w5}}, d_{G_{w6}}$

where ${}^I \alpha$ refers to the angular acceleration of the base IMU. If the base IMU undergoes constant local linear and angular velocity motion, the angular velocity of the auxiliary IMU ${}^I_a \boldsymbol{\omega}$ is also constant [see Eq.(145)]. The ${}^I \mathbf{a}$ and ${}^I \alpha$ of the base IMU should be zeros. Hence, Eq. (146) yields:

$${}^I_a \mathbf{a} = {}^I_a \mathbf{R} ([{}^I \boldsymbol{\omega}] [{}^I \boldsymbol{\omega}] {}^I \mathbf{p}_{I_a}) \quad (147)$$

If ${}^I \boldsymbol{\omega}$ is constant but not zero, the local linear acceleration ${}^I_a \mathbf{a}$ should not be zero. This breaks the local constant linear velocity assumption for the auxiliary IMU. Furthermore, we find that the norm of ${}^I_a \mathbf{v}$ is constant:

$${}^I_a \mathbf{v} = {}^I_a \mathbf{R} ({}^I \mathbf{v} + [{}^I \boldsymbol{\omega}] {}^I \mathbf{p}_{I_a}) \quad (148)$$

But the non-zero acceleration ${}^I_a \mathbf{a}$ will cause the bearing change of local velocity, which makes the time offset between the base and auxiliary IMUs observable. This is further verified through our simulation results (see Fig. 6), while interested readers refer to our companion technical report (Yang et al. 2023a) for the unobservable directions.

9.2 Intrinsic for Auxiliary Inertial Sensors

In our previous work (Yang et al. 2023b, 2020b), the degenerate motions of IMU intrinsic for mono-VINS system have been studied. In this work, we have found that the degenerate motion primitives in (Yang et al. 2023b) still hold for the auxiliary IMU intrinsic with our inertial model choice (see Table 3). Note that fully excited motions are needed in order to make all intrinsic parameters observable for the base/auxiliary IMUs/gyroscopes. We will discuss this mainly in the following simulations and experiments.

10 Simulation Results

The simulator, which is provided within the OpenVINS project (Geneva et al. 2020) along with the multi-IMU extension from (Eckenhoff et al. 2021) and IMU intrinsic extension (Yang et al. 2023b), is leveraged to provide synthetic measurements with perfect groundtruth for verification of the proposed MVIS under different motion conditions. In the simulation, one base IMU IMUb, one




Figure 2. Simulated trajectories. Left: *calib_3d* with fully excited 3D motion, total length: 89.4 m; Middle: *tum_room* with 1 axis rotation and 3D translation, total length: 134.5 m; Right: *circle_planar* with circular planar motion (constant z and only yaw rotation), total length: 157.1 m. The green triangle and red circle denote the beginning and ending of these trajectories, respectively.




Figure 3. Simulation results for *fully-excited motion*. All the cameras (CAM0 and CAM1) related parameters converge nicely. 3σ bounds (dashed line) and estimation errors (solid line) are plotted for five different runs (shown in different colors) with different initial calibration perturbations.

Table 4. Simulation parameters and prior standard deviations that perturbations of measurements and initial states were drawn from.

Parameter	Value	Parameter	Value
IMU DW	0.003	IMU Da	0.003
Rot. atol (rad)	0.003	IMU Tg	0.001
Gyro. White Noise ($\text{rad s}^{-1} \sqrt{\text{Hz}^{-1}}$)	1.6968e-04	Gyro. Rand. Walk ($\text{rad s}^{-2} \sqrt{\text{Hz}^{-1}}$)	1.9393e-05
Accel. White Noise ($\text{m s}^{-2} \sqrt{\text{Hz}^{-1}}$)	2.0000e-3	Accel. Rand. Walk ($\text{m s}^{-3} \sqrt{\text{Hz}^{-1}}$)	3.0000e-3
Focal Len. (px/m)	1.0	Cam. Center (px)	1.0
d3 and d4	0.002	d3 and d4	0.002
Rot. CtoI (Hz)	0.004	Pos. IinC (m)	0.008
Pixel Proj. (px)	1	Cam-IMU Timeoff (s)	0.008
IMU-IMU Timeoff (s)	0.003	Gyro-IMU Timeoff (s)	0.003
Rot. AltoBI (rad)	0.003	Pos. Iainlb (m)	0.005
Cam Freq. (Hz)	10 / 10 / 10	IMU Freq. (Hz)	250 / 300 / 200

auxiliary IMU IMUa0, one auxiliary gyroscope IMUa1, one global shutter (GS) camera CAM0 and one rolling shutter (RS) camera CAM1 are simulated. The basic configuration of the simulator is listed in Table 4. The three trajectories used for the simulation Fig. 2 are as follows:

- Fully-excited motion (shown in the right of Fig. 2): All axes of the accelerometer and gyroscope are fully excited with a general 3D handheld trajectory.
- One-axis motion (shown in the middle of Fig. 2): The sensor suite moves in 3D space but with only yaw rotation. The trajectory is modified based on *tum_room1* from (Schubert et al. 2018).

- Circular-planar motion (shown in the left of Fig. 2): The sensor suite moves in x - y plane with constant local angular and linear velocities.

Specifically, we first build a B-spline with trajectory keypoints from base IMU. Then, we can compute the acceleration of base IMU by calculating double derivatives for the position component of the B-spline at specified time stamp. We leverage rigid body constraints between base and auxiliary IMU to simulate the auxiliary IMU readings. The base IMU acceleration can be transferred to the auxiliary IMU frame with the groundtruth angular velocity and acceleration, which are also computed from derivatives of base IMU B-spline. The angular velocity of the auxiliary IMU can be simply computed with angular velocity from base IMU and the rigid rotation between based IMU and auxiliary IMU. Then white Gaussian noises are added to the auxiliary IMU readings based on Eq. (1) and Eq. (2).

To simulate RS visual bearing measurements, we follow the same logic in (Yang et al. 2023b). Static environmental features are first generated along the trajectory at random depths and bearings. Then, for a given imaging time, we project each feature in view into the current image frame using the true camera intrinsic and distortion model and find the corresponding observation row. Given this projected row and image time, we can find the pose at which that RS




Figure 4. Simulation results for *fully-excited motion*. All the base IMU (IMUb) and auxiliary IMUs (IMUa0, IMUa1) related parameters converge nicely. 3σ bounds (dashed line) and estimation errors (solid line) are plotted for five different runs (shown in different colors) with different initial calibration perturbations.




Figure 5. Simulation results for *One-axis motion*. The translation of CAM0-IMUb (y component) and IMUa0-IMUb (z component), the rotation of IMUa1-IMUb (z component), the d_{w1} , d_{w2} and d_{w3} of IMUb, IMUa0 and IMUa1 show inability to converge (sigma bound does not decrease due to no information gain). 3σ bounds (dashed line) and estimation errors (solid line) are plotted for five different runs (shown in different colors) with different initial calibration perturbations.

row should have been exposed. We can then re-project this feature into the new pose and iterate until the projected row does not change (which typically requires 2-3 iterations). We now have a feature measurement which occurs at the correct pose given its RS row. This measurement is then corrupted with white noise. The imaging timestamp corresponding to the starting row is then shifted by the true IMU-camera time offset t_d to simulate cross-sensor delay. In the following simulations, the RPNG IMU model [see Section 3.1] is used to be aligned with the analysis.

It is important to note that, in the following, we only present the most prominent results due to space limits, while comprehensive simulation and experimental results can be found in our companion technical report (Yang et al. 2023a).

10.1 Fully-Excited Motion

We first evaluate the proposed system on a general 3D handheld trajectory, see Fig. 2, which fully excites all 6 axes of the sensor platform. To save space, only selected parameters are present, but all parameters are perturbed and




Figure 6. Simulation results for *Circular-planar motion*. The translation of CAM0-IMUb, CAM1-IMUb, IMUa0-IMUb, the rotation of IMUa1-IMUb, the time offset of CAM0-IMUb, CAM1-IMUb and IMUa1-IMUb all show inability to converge (sigma bound does not decrease due to no information gain). Note that the RS readout time of CAM1 and the time offset of IMUa0-IMUb converge slower due to less motion excitation. 3σ bounds (dashed line) and estimation errors (solid line) are plotted for five different runs (shown in different colors) with different initial calibration perturbations.




Figure 7. Simulation results for *Circular-planar motion*. The gyroscope and acceleration related parameters (\mathbf{D}_w , \mathbf{D}_a and \mathbf{T}_g) for both base and auxiliary IMUs do not converge or converge much slower than the case of fully-excited motions. 3σ bounds (dashed line) and estimation errors (solid line) are plotted for five different runs (shown in different colors) with different initial calibration perturbations.

estimated during our simulation runs. The camera related results are shown in Fig. 3 while the IMU related results are shown in Fig. 4. For each figure, there are five different runs with different initial state perturbations.

It is clear that all parameters are able to converge towards the true value within the first 20-40 seconds of the trajectory, which verifies our conclusion that all the calibration parameters for MVIS are observable given fully-excited motions. These results also verify that the proposed

MVIS indeed is able to perform calibration of all parameters for visual and inertial sensors.

10.2 Degenerate One-Axis Motion

We now perform a simulation where the trajectory only exhibits one-axis rotation about the global z-axis to verify our identified degenerate motion. We generate a sinusoidal trajectory such that the roll and pitch of the orientation does not change over the trajectory (thus yaw only rotation), see

Fig. 2. Shown in Fig. 5, multiple parameters are unable to converge with either estimation errors or estimation uncertainties (3σ bounds). This matches the parameters which we have identified as unobservable under this motion. We can see that the 3 parameters d_{w1} , d_{w2} and d_{w3} for both the base IMU IMUb, auxiliary IMU IMUa0, and auxiliary gyroscope IMUa1 are unable to be calibrated. Additionally, the y component for the rigid position between the camera to base IMU (CAM0-IMUb Pos.) cannot converge at all. The z component for the position of the auxiliary IMU to base IMU (IMUa0-IMUb Pos.) is unable to be calibrated as expected. Note that the y component of ${}^I\mathbf{p}_C$ and the z component of ${}^I\mathbf{p}_{I_a}$ are all along the rotation axis which is degenerate.

Furthermore, it can be seen that we are unable to calibrate a portion of the relative rotation between the base IMU and auxiliary gyroscope (IMUa1-IMUb Ori.) due to one-axis rotation, which can be calibrated nicely in the fully-excited motion case. This further confirms our degenerate motion analysis summarized in Table 2.

10.3 Degenerate Circular-Planar Motion

We also perform a simulation where the sensors follow a circular-planar motion shown in Fig. 2. This is a typical example motion of constant angular and linear velocity. The translation and the time offset of CAM0-IMUb, CAM1-IMUb, the translation of IMUa0-IMUb and the orientation of IMUa1-IMUb are not observable. Hence, their 3σ bounds and estimate errors are kept as almost straight lines and do not converge at all. These results further verifies our identified degenerate motions shown in Table 2.

The time offset between auxiliary gyroscope and based IMU (IMUa1-IMUb Toff) cannot be calibrated since its 3σ bounds and estimation errors do not converge at all. However, the time offset between auxiliary IMU to base IMU (IMUa0-IMUb Toff) is still observable, given that both the estimation errors have converged in Fig. 6, which verifies our degenerate motion analysis in Section 9.1.5. Note that the rolling shutter readout time of the CAM1 converges quite slowly, given that the sensor motion is not fully excited.

The calibration results for IMU related intrinsics are shown in Fig. 7. It is clear that the gyroscope related parameters \mathbf{D}_w and the accelerometer related parameters \mathbf{D}_a do not converge at all. The convergence of g-sensitivity \mathbf{T}_g also becomes much worse compared to fully excited motion in Fig. 4 which results from fully-excited motions.

11 Experimental Results

The proposed self-calibration system is further evaluated using our own visual-inertial sensor rig (VI-Rig) as shown in Fig. 8. Specifically, it contains a MS-GX-25, MS-GX-35, Xsens MTi 100, FLIR blackfly camera, RealSense T265 tracking camera which contains an integrated BMI055 IMU along with a fisheye stereo global shutter camera, and 640x480 ELP-960P2CAM-V90-VC USB 2.0 RS-stereo camera. We perform three sets of experiments[†].

- Fully-excited motion with 4 IMUs + 3 GS Cameras.
- Fully-excited motion with 4 IMUs + 2 GS Cameras + 2 RS Cameras.
- Planar motion with 4 IMUs + 2 GS cameras.




Figure 8. The self-assembled sensor rigs in real-world experiments, containing one Microstrain GX-25, one MicroStrain GX-35, one MTI Xsens IMU, one BalckFly camera, one IntelRealsense T265 tracking camera (with a GS fisheye stereo camera and an BMI055 IMU inside) and one ELP stereo RS camera.

In these experiments, we evaluate the intrinsic calibration with Kalibr model [see Section 3.1], in order to have fair comparison to Kalibr calibration toolbox (Furgale et al. 2013), for commonly used IMUs, including both high-end and low-end brands. We also investigate the joint calibration performances for IMU/Camera with regarding to the different number of cameras and different setup of IMUs. In addition, planar motion, one of the most commonly seen degenerate motions, is also investigated to show its effects on calibration parameters, the results of which further verifies our degeneration motion analysis.

11.1 4 IMUs + 3 GS

All the four IMUs, FLIR blackfly camera and the GS stereo camera from RealSense T265 are used for this evaluation. All cameras used in this experiments are not rolling shutter to ensure fair comparison against the baseline Kalibr (Furgale et al. 2013) which only supports IMU-Camera calibration with global shutter cameras. Total 10 datasets were collected with an AprilTag board, on which both the proposed system and the Kalibr calibration toolbox were run to evaluate the calibration accuracy and repeatability statistics on all calibration parameters. During data collection, all 6-axis motion of the VI-Rig were excited to avoid degenerate motions for calibration parameters.

11.1.1 Calibration with Different Number of Cameras

When running Kalibr, all the IMUs and cameras are used to achieve the best calibration results from Kalibr. When running our proposed MVIS, we use all the four IMUs with 1/2/3 camera, respectively. In this way, we can evaluate how the number of used cameras affect the calibration performance.

The final converged estimates of the calibration parameters from both systems on these 10 datasets can be shown in the box plots in Fig. 9. The proposed MVIS was run with one (green), two (black), and three (blue) of the cameras. The baseline Kalibr (magenta) was run on all three cameras. The x-axis of figures in the second and third row denotes the

[†]Datasets are available at <https://openmvis.com/>.




Figure 9. Calibration Results for CAM0 and four IMUs related parameters over 10 datasets collected with Intel Realsense T265 (GS), FLIR Blackfly camera (GS) and four IMUs. The proposed MVIS was run with one (green), two (black), and three (blue) of the cameras. The baseline Kalibr (magenta) was run on all three cameras and all four IMUs. The x-axis of figures in the second and third row denotes the base IMU (IMUb) as b and auxiliary IMU (IMUa0-IMUa2) as 0, 1 and 2 respectively. Note that the calibration convergence of camera/IMU intrinsics and camera to IMU translation are improved if more cameras are used.




Figure 10. Calibration results over 15 different datasets collected with Intel Realsense T265 (GS), ELP-960P2CAM-V90-VC USB 2.0 (RS, 640x480) and four IMUs. The proposed MVIS (blue, using all the sensors) and Kalibr baseline (magenta, using only T265 cameras with all the IMUs) statistics are reported. The top x-axis denote the two global shutter cameras (CAM0, CAM1) as 0 and 1, respectively; The bottom a-axis denotes the base IMU (IMUb) as b, and auxiliary IMUs (IMUa0, IMUa1 and IMUa2) as 0, 1 and 2, respectively.




Figure 11. Calibration results over 15 different datasets collected with Intel Realsense T265 (GS), ELP-960P2CAM-V90-VC USB 2.0 (RS, 640x480) and four IMUs. The proposed MVIS (blue, using all the sensors) and Kalibr rolling shutter baseline (magenta, using only the RS cameras with all IMUs) statistics are reported. The top x-axis denote the two rolling shutter cameras (CAM2, CAM3) as 2 and 3, respectively; The bottom a-axis denotes the base IMU (IMUb) as b, and auxiliary IMUs (IMUa0, IMUa1 and IMUa2) as 0, 1 and 2.

base IMU (GX-25 IMUb) as b and auxiliary IMU (GX-35 IMUa0, Xsens IMUa1, T265 IMU IMUa2) as 0, 1 and 2 respectively. Note that the camera intrinsics are required to be fixed for Kalibr when performing IMU-Camera calibration. Hence there is only one value for each camera intrinsics is shown in Fig. 9.

The range of the boxplot in the figure indicates the convergence of calibration parameters. The proposed MVIS needs initial guess for the calibration parameters to start the optimization. As shown in the first row of Fig. 9, the initial guess distribution for the calibration parameters are presented with converged estimated values. The initial guess for d_2 of CAM0 distortion model is within ± 0.5 while the




Figure 12. Temporal calibration results over 15 different datasets with Intel Realsense T265 (GS), ELP-960P2CAM-V90-VC USB 2.0 (RS, 640x480) and four IMUs. The proposed MVIS (blue) and Kalibr rolling shutter baseline (magenta) statistics are reported. The x-axis of the left 3 figures denotes the two global shutter camera CAM0, CAM1, two rolling shutter camera CAM2, CAM3. The x-axis of the right figure denotes the time offsets between the base IMU (IMUb), and auxiliary IMUs (IMUa0, IMUa1, IMUa2).




Figure 13. Calibration results over 15 different datasets with Intel Realsense T265 and four IMUs. The proposed MVIS with a base IMU and only gyroscopes of the 3 auxiliary IMUs (black), MVIS with a base IMU and 3 auxiliary IMUs (blue) and Kalibr baseline (magenta) statistics are reported. The top x-axis denotes the base IMU (IMUb) and auxiliary IMUs (IMUa0, IMUa1, IMUa2) for all algorithms.

final estimated values are between 0 and 0.1. The initial guess for time offset for CAM0-IMUb is within ± 5 ms, while the final converged values from the proposed MVIS are most cases around ± 0.5 ms. These results show that the calibration parameters can converge robustly within the proposed MVIS.

It can be observed from Fig. 9 that the calibration estimation convergence of IMU/camera intrinsics and CAM0-IMUb translation are better in blue color than those in green or black colors, which indicate that more cameras can be used to improve overall calibration uncertainties. This is probably due to improved visual feature estimates from longer feature tracks or wider field-of-view due to multi-view constraints when more cameras are used in the experiment.

11.1.2 Comparison with Kalibr By comparing the mean values of each boxplot in Fig. 9, it can be seen that the MVIS can achieve comparable calibration results to Kalibr, which verifies the calibration accuracy of the proposed MVIS.

By evaluating the IMU calibration results across the four IMUs of IMUb, IMUa0, IMUa1 and IMUa2 (denoted as b, 0, 1, 2 in the second and third row in Fig. 9) used in the experiments, we clearly see that IMUa2, a relatively low-cost BMI055 IMU, demonstrates larger scale correction for gyroscope and accelerometer than other three high-end IMUs (GX-25 IMUb, GX-35 IMUa0 and Xsens IMUa1). This is expected as the IMUb, IMUa0 and IMUa1 are supposed to have more stable and sophisticated factory calibration than IMUa2. This result, aligned with our previous work for single-IMU-camera calibration (Yang et al. 2023b), further validates the proposed MVIS can generate reasonable and accurate calibration for IMUs.

Note that we have also implemented both numerical and analytical Jacobians for the proposed MVIS. The numerical and analytical Jacobians can achieve similar accuracy results but with 10-14% running time saving when using analytical Jacobians.

11.2 4 IMUs + 2 GS + 2 RS

All the four IMUs, GS stereo camera from RealSense T265 and ELP RS stereo camera are used in this evaluation. Both GS and RS cameras are used in this experiment to show that our proposed MVIS supports full-parameter joint calibration with GS and RS cameras, while Kalibr does not support joint calibration of IMU and rolling shutter cameras. Total 15 datasets were collected with an AprilTag board, on which both the proposed MVIS and the Kalibr calibration toolbox were run to report calibration accuracy and repeatability statistics. During data collection, all 6-axis motion of the VI-Rig were excited to avoid degenerate motions for calibration parameters.

11.2.1 Calibration for IMU and GS/RS During evaluation, all the GS/RS cameras and IMUs are used for the proposed MVIS. Since Kalibr does not support hybrid calibration of GS and RS cameras, we first run Kalibr with all four IMUs and only GS stereo camera from RealSense T265 (CAM0&CAM1). The results with boxplots are presented in Fig. 10. Then, we run Kalibr with all four IMUs and ELP RS stereo camera (CAM2&CAM3) using a Kalibr extension (Huai et al. 2022). The results are presented in Fig. 11. In this experiment, we also evaluate the calibration of multiple auxiliary gyroscopes of the proposed MVIS by using only the gyroscopes of all the auxiliary IMUs. The calibration results are shown in Fig. 13. Note that in the evaluations, the left&right cameras from the stereo of RealSense T265 are denoted as CAM0&CAM1, while the left&right cameras from ELP RS stereo are denoted as CAM2&CAM3. In this experiment, we did camera calibration for each collected dataset with Kalibr. Therefore, we can have the statistics for the camera intrinsic estimates in Fig. 10 and 11, from which, we can see that the mean estimates of both the IMU and camera related parameters are similar for both the proposed MVIS and Kalibr.

The boxplot ranges of camera and IMU related parameters from the proposed MVIS are much smaller than those of the Kalibr, which shows that MVIS is able to achieve much better estimation convergence and repeatability than Kalibr, especially for the case of using ELP RS cameras. This result verifies that the proposed MVIS can handle the joint

calibration of IMU-GS/RS cameras, which is missing from Kalibr.

In this experiment, the MVIS uses both GS/RS cameras while the Kalibr is evaluated on GS or RS cameras only. Hence, this experiment further proves that the joint calibration of multiple sensors (i.e. cameras) does improve the calibration accuracy and repeatability.

It is interesting to see that the IMU calibration results (the scales for \mathbf{D}_w and \mathbf{D}_a) between these two experiments (Fig. 9 in Section 11.1 and Fig. 10 or Fig. 11 in Section 11.2) are very similar. This further validates the stability of the proposed MVIS.

11.2.2 Evaluation of Multiple Gyroscopes Calibration

We further evaluate the proposed MVIS with multiple auxiliary gyroscopes. With the same 15 datasets, all cameras, base IMU (GX-25 IMUb) and the gyroscopes of three auxiliary IMUs (GX-35 IMUa0, Xsens IMUa1 and T265 IMU IMUa2) are used for evaluation with MVIS. The calibration results of MVIS with these auxiliary gyroscopes (in black), compared to the MVIS (in blue) and Kalibr (in magenta) with full auxiliary IMUs, are shown in Fig. 13. Note that the auxiliary gyroscope does not contain ${}^I_w\mathbf{R}$. Hence, we set ${}^I_w\mathbf{R} = \mathbf{I}_3$ as default.

It is clear from the results that MVIS with multiple auxiliary gyroscopes still can achieve almost the same estimates for gyroscope scales and time offsets as MVIS and Kalibr with full auxiliary IMUs.

At the same time, we can also find out that the calibration of rotation between auxiliary gyroscope and base IMU (the second row of Fig. 13) from MVIS with multiple gyroscopes, is slightly worse than that of MVIS and Kalibr with full IMUs, especially for IMUa2. This might be due to the fact that accelerometer measurement can benefit the extrinsic calibration between IMUs. We also want to point out that the rotation calibration difference is smaller than 0.5° , which is not significant.

11.2.3 Temporal Calibration The temporal calibration, including time offsets and rolling shutter readout time, are presented in Fig. 12. The 0, 1, 2 and 3 from the CAM *Toff* and Readout refers to CAM0 - CAM3. From Fig. 12, it is clear that the time offset calibration is almost the same for the proposed MVIS and the Kalibr. The readout time calibration errors are all within 2 ms.

From the results, we can also find out that the triggering time offset of the RealSense T265 is not stable. As can be seen from the left of Fig. 12, there are outliers as large as 30 ms between the base IMU IMUb and the right camera of T265. Similarly, the time offset of the IMU from T265 (IMUa2) to base IMU (IMUb) is also slightly unstable from the estimates of MVIS and Kalibr, as outliers (red crosses) in right of Fig. 12. Note that the 0, 1 and 2 in the plot of IMU *Toff* from right of Fig. 12 denote the time offsets of IMUa0, IMUa1 and IMUa2 to IMUb, respectively.

As shown in the right of Fig. 12 and the bottom right of Fig. 13, the time offset between based IMU IMUb and the auxiliary IMU IMUa2 (BMI055 from T265) also has 10 ms offsets (from near -5 ms to 5 ms). This is probably due to the build-in drivers of this low-cost sensor rigs. From these figs, we can see that both the estimate results from Kalibr (magenta) and the proposed MVIS (blue) can identify

the problems of the temporal calibration of T265, which validates that the proposed MVIS can be used to identify the temporal instability of T265 and provide reliable calibration results.

11.3 Verification of Degenerate Motion

We further verify the degenerate motions with a dataset collected under planar motion. All four IMUs and the GS stereo camera from RealSense T265 are used for data collection. When collecting data, the VI-Rig is put on a chair with wheels and performs planar motion. The proposed MVIS are run on this dataset 4 times with different perturbations to the initial values of IMU-IMU translations.

Under planar motion, the rotation axis is fixed for the VI-Rig. Hence, the IMU-IMU translation along the rotation axis and the d_{w1} , d_{w2} , d_{w3} from \mathbf{D}_w are unobservable. The calibration results for these parameters can be clearly seen in Fig. 14 and they diverge erroneously during optimization.

As a comparison, we use the same sensor rig and same perturbations to IMU-IMU translation to run the proposed MVIS under fully-excited motions. The calibration results are shown in Fig. 15. It is clear that all these calibration parameters can converge nicely compared to Fig. 14 when fully-excited motions are given.

12 Conclusions and Future Work

In this paper, we have developed a multi-visual-inertial system (MVIS) estimation algorithm which can fuse multiple IMUs, gyroscopes and GS/RS cameras, with a special focus on full-calibration of all intrinsics, extrinsics, and temporal parameters (including time offsets and readout times for RS cameras). In particular, we proposed ACI³, a novel IMU pre-integration, to incorporate IMU intrinsic parameters. Based on ACI³, we fuse multiple IMU measurements by leveraging IMU-IMU rigid body constraints with spatial-temporal and inertial intrinsic calibration. We have performed MVIS observability analysis, proving that four standard unobservable directions corresponding to global yaw and global translation remain, while the calibration parameters are observable under fully excited motion. Moreover, we have also, for the first time, identified the commonly seen degenerate motions that can cause IMU-IMU/gyroscope calibration unobservable. We show that the rotation calibration between IMU and gyroscopes is unobservable given one-axis rotation, while the time offset between IMUs is observable given constant local angular and linear velocity for one of the IMUs.

Extensive simulations have been performed to evaluate the proposed system and verify the degenerate motions identified for these calibration parameters. Moreover, a self-made sensor rig that consists of multiple commonly-used IMUs and GS/RS cameras were used for data collection and system evaluation. In particular, three sets of experiments were performed to fully evaluate the calibration accuracy of the proposed MVIS against Kalibr, one of the state-of-art sensor calibration benchmark. Total 25 datasets collected with the VI-Rigs are evaluated to provide detailed statistics for calibration convergence and repeatability of the proposed MVIS and Kalibr.




Figure 14. Calibration results for one planar motion dataset collected with Intel Realsense T265 and four IMUs. The translation of IMUb-IMUa0, IMUb-IMUa1, IMUb-IMUa2, the D_w of IMUb, IMUa0, IMUa1 and IMUa2 cannot converge under planar motions, which verifies our observability analysis. Different colors represent different initial perturbations to the IMU-IMU translations.




Figure 15. Calibration results for one fully-excited motion dataset collected with Intel Realsense T265 and four IMUs. The translation of IMUb-IMUa0, IMUb-IMUa1, IMUb-IMUa2, the D_w of IMUb, IMUa0, IMUa1 and IMUa2 converge nicely compared to planar motion case. Different colors represent different initial perturbations to the IMU-IMU translations.

In the future, we will address how to calibrate MVIS under degenerate motions (e.g., on ground or aerial vehicles), and develop efficient marginalization to enable the proposed batch optimization-based MVIS with online calibration amenable for real-time performance.

Acknowledgements

This work was partially supported by the University of Delaware (UD) College of Engineering, the NSF (IIS-1924897), and Google ARCore. Yang was partially supported by the University Doctoral Fellowship and Geneva was partially supported by the University Doctoral Fellowship.

References

- Barfoot TD (2017) *State estimation for robotics*. Cambridge University Press.
- Bloesch M, Omari S, Hutter M and Siegwart R (2015) Robust visual inertial odometry using a direct ekf-based approach. In: *2015 IEEE/RSJ international conference on intelligent robots and systems (IROS)*. IEEE, pp. 298–304.
- Campos C, Elvira R, Rodríguez JGG, Montiel JM and Tardós JD (2021) ORB-SLAM3: An accurate open-source library for visual, visual-inertial, and multimap slam. *IEEE Transactions on Robotics*.
- Chirikjian GS (2011) *Stochastic models, information theory, and Lie groups, volume 2: Analytic methods and modern applications, volume 2*. Springer Science & Business Media.
- Dellaert F (2012) Factor graphs and gtsam: A hands-on introduction. Technical report, Georgia Institute of Technology.
- Eckenhoff K, Geneva P and Huang G (2019a) Closed-form preintegration methods for graph-based visual-inertial navigation. *International Journal of Robotics Research* 38(5): 563–586.
- Eckenhoff K, Geneva P and Huang G (2019b) Sensor-failure-resilient multi-imu visual-inertial navigation. In: *Proc. International Conference on Robotics and Automation*. Montreal, Canada.
- Eckenhoff K, Geneva P and Huang G (2021) MIMC-VINS: A versatile and resilient multi-imu multi-camera visual-inertial navigation system. *IEEE Transactions on Robotics*.
- Faizullin M and Ferrer G (2023) Best axes composition extended: Multiple gyroscopes and accelerometers data fusion to reduce systematic error. *Robotics and Autonomous Systems* 160: 104316. DOI:https://doi.org/10.1016/j.robot.2022.104316. URL <https://www.sciencedirect.com/science/article/pii/S0921889022002056>.
- Forster C, Carlone L, Dellaert F and Scaramuzza D (2016) On-manifold preintegration for real-time visual-inertial odometry. *IEEE Transactions on Robotics* 33(1): 1–21.
- Fu B, Han F, Wang Y, Jiao Y, Ding X, Tan Q, Chen L, Wang M and Xiong R (2021) High precision multi-camera assisted camera-imu calibration: Theory and method. *IEEE Transactions on Instrumentation and Measurement*.
- Furgale P, Rehder J and Siegwart R (2013) Unified temporal and spatial calibration for multi-sensor systems. In: *2013 IEEE/RSJ*

- International Conference on Intelligent Robots and Systems*. IEEE, pp. 1280–1286.
- Geneva P, Eckenhoff K, Lee W, Yang Y and Huang G (2020) Openvins: A research platform for visual-inertial estimation. In: *Proc. of the IEEE International Conference on Robotics and Automation*. Paris, France. URL https://github.com/rpng/open_vins.
- Guo C, Kottas D, DuToit R, Ahmed A, Li R and Roumeliotis S (2014) Efficient visual-inertial navigation using a rolling-shutter camera with inaccurate timestamps. Berkeley, CA.
- Hesch JA, Kottas DG, Bowman SL and Roumeliotis SI (2014) Consistency analysis and improvement of vision-aided inertial navigation. *IEEE Transactions on Robotics* 30(1): 158–176.
- Huai J, Zhuang Y, Lin Y, Jozkow G, Yuan Q and Chen D (2022) Continuous-time spatiotemporal calibration of a rolling shutter camera-imu system. *IEEE Sensors Journal* 22(8): 7920–7930. DOI:10.1109/JSEN.2022.3152572.
- Huang G (2012) *Improving the Consistency of Nonlinear Estimators: Analysis, Algorithms, and Applications*. PhD Thesis, Department of Computer Science and Engineering, University of Minnesota. URL <https://conservancy.umn.edu/handle/11299/146717>.
- Huang G (2019) Visual-inertial navigation: A concise review. In: *Proc. International Conference on Robotics and Automation*. Montreal, Canada.
- Jadid A, Rudolph L, Pankratz F and Klinker GJ (2019) Utilizing multiple calibrated imus for enhanced mixed reality tracking. *2019 IEEE International Symposium on Mixed and Augmented Reality Adjunct (ISMAR-Adjunct)* : 384–386.
- Kim D, Shin S and Kweon IS (2017) On-line initialization and extrinsic calibration of an inertial navigation system with a relative preintegration method on manifold. *IEEE Transactions on Automation Science and Engineering* 15(3): 1272–1285.
- Kuo J, Muglikar M, Zhang Z and Scaramuzza D (2020) Redesigning slam for arbitrary multi-camera systems. In: *2020 IEEE International Conference on Robotics and Automation (ICRA)*. IEEE, pp. 2116–2122.
- Lee J, Hanley D and Bretl T (2022) Extrinsic calibration of multiple inertial sensors from arbitrary trajectories. *IEEE Robotics and Automation Letters* 7(2): 2055–2062. DOI:10.1109/LRA.2022.3143290.
- Lee W, Eckenhoff K, Yang Y, Geneva P and Huang G (2020) Visual-inertial-wheel odometry with online calibration. In: *Proc. of the IEEE/RSJ International Conference on Intelligent Robots and Systems*. Las Vegas, NV.
- Leutenegger S, Lynen S, Bosse M, Siegwart R and Furgale P (2015) Keyframe-based visual-inertial odometry using nonlinear optimization. *The International Journal of Robotics Research* 34(3): 314–334.
- Li M, Yu H, Zheng X and Mourikis AI (2014) High-fidelity sensor modeling and self-calibration in vision-aided inertial navigation. In: *2014 IEEE International Conference on Robotics and Automation (ICRA)*. IEEE, pp. 409–416.
- Martinelli A (2013) Observability properties and deterministic algorithms in visual-inertial structure from motion. *Foundations and Trends in Robotics* : 1–75.
- Mourikis AI and Roumeliotis SI (2007) A multi-state constraint kalman filter for vision-aided inertial navigation. In: *Proceedings 2007 IEEE International Conference on Robotics and Automation*. IEEE, pp. 3565–3572.
- OpenCV Developers Team (2021) Open source computer vision (OpenCV) library. Available: <http://opencv.org>.
- Paul MK, Wu K, Hesch JA, Nerurkar ED and Roumeliotis SI (2017) A comparative analysis of tightly-coupled monocular, binocular, and stereo vins. In: *2017 IEEE International Conference on Robotics and Automation (ICRA)*. IEEE, pp. 165–172.
- Qin T, Li P and Shen S (2018) Vins-mono: A robust and versatile monocular visual-inertial state estimator. *IEEE Transactions on Robotics* 34(4): 1004–1020.
- Rehder J, Nikolic J, Schneider T, Hinzmann T and Siegwart R (2016) Extending kalibr: Calibrating the extrinsics of multiple imus and of individual axes. In: *2016 IEEE International Conference on Robotics and Automation (ICRA)*. IEEE, pp. 4304–4311.
- Schneider T, Li M, Cadena C, Nieto J and Siegwart R (2019) Observability-aware self-calibration of visual and inertial sensors for ego-motion estimation. *IEEE Sensors Journal* 19(10): 3846–3860.
- Schubert D, Goll T, Demmel N, Usenko V, Stückler J and Cremers D (2018) The tum vi benchmark for evaluating visual-inertial odometry. In: *2018 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*. pp. 1680–1687. DOI: 10.1109/IROS.2018.8593419.
- Sola J (2017) Quaternion kinematics for the error-state kalman filter. *arXiv preprint arXiv:1711.02508* .
- Sun K, Mohta K, Pfrommer B, Watterson M, Liu S, Mulgaonkar Y, Taylor CJ and Kumar V (2018) Robust stereo visual inertial odometry for fast autonomous flight. *IEEE Robotics and Automation Letters* 3(2): 965–972.
- Trawny N and Roumeliotis SI (2005) Indirect kalman filter for 3d attitude estimation. *University of Minnesota, Dept. of Comp. Sci. & Eng., Tech. Rep* 2: 2005.
- Usenko V, Engel J, Stückler J and Cremers D (2016) Direct visual-inertial odometry with stereo cameras. In: *2016 IEEE International Conference on Robotics and Automation (ICRA)*. IEEE, pp. 1885–1892.
- Wu KJ, Guo CX, Georgiou G and Roumeliotis SI (2017) Vins on wheels. In: *2017 IEEE International Conference on Robotics and Automation (ICRA)*. IEEE, pp. 5155–5162.
- Wu Y, Kuang J and Niu X (2023) Wheel-ins2: Multiple mems imu-based dead reckoning system with different configurations for wheeled robots. *IEEE Transactions on Intelligent Transportation Systems* 24(3): 3064–3077. DOI:10.1109/TITS.2022.3220508.
- Yang Y, Babu BPW, Chen C, Huang G and Ren L (2020a) Analytic combined imu integration for visual-inertial navigation. In: *Proc. of the IEEE International Conference on Robotics and Automation*. Paris, France.
- Yang Y, Geneva P, Eckenhoff K and Huang G (2019) Degenerate motion analysis for aided INS with online spatial and temporal calibration. *IEEE Robotics and Automation Letters (RA-L)* 4(2): 2070–2077.
- Yang Y, Geneva P and Huang G (2023a) Multi-visual-inertial sensor calibration: Algorithm and analysis. Technical Report RPNG-2021-MVIS, University of Delaware. URL https://yangyulin.net/papers/2021_techreport_MVIS.pdf.
- Yang Y, Geneva P, Zuo X and Huang G (2020b) Online imu intrinsic calibration: Is it necessary? In: *Proc. of the Robotics: Science*

and Systems. Paris, France.

Yang Y, Geneva P, Zuo X and Huang G (2023b) Online self-calibration for visual-inertial navigation: Models, analysis, and degeneracy. *IEEE Transactions on Robotics* : 1–20DOI:10.1109/TRO.2023.3275878.

Yang Y and Huang G (2019) Observability analysis of aided ins with heterogeneous features of points, lines and planes. *IEEE Transactions on Robotics* 35(6): 399–1418.

Zhang L, Wisth D, Camurri M and Fallon M (2022) Balancing the budget: Feature selection and tracking for multi-camera visual-inertial odometry. *IEEE Robotics and Automation Letters* 7(2): 1182–1189. DOI:10.1109/LRA.2021.3137910.

Zhang M, Xu X, Chen Y and Li M (2020) A lightweight and accurate localization algorithm using multiple inertial measurement units. *IEEE Robotics and Automation Letters* 5(2): 1508–1515.

Zhi X, Hou J, Lu Y, Kneip L and Schwertfeger S (2022) Multical: Spatiotemporal calibration for multiple imus, cameras and lidars. In: *2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*. pp. 2446–2453. DOI: 10.1109/IROS47612.2022.9982031.

A IMU Readings

$$\begin{aligned}\omega_{k+i} &= {}^I_w \mathbf{RD}_w ({}^w \omega_{m_{k+i}} - \mathbf{T}_g \mathbf{a}_{k+i} - \mathbf{b}_{g_{k+i}} - \mathbf{n}_{g_{k+i}}) \\ &= {}^I_w \mathbf{RD}_w ({}^w \omega_{m_{k+i}} - \mathbf{b}_{g_{k+i}} - \mathbf{n}_{g_{k+i}} - \mathbf{T}_g \mathbf{a}_{k+i}) \\ &= {}^I_w \mathbf{RD}_w ({}^w \omega_{m_{k+i}} - \Delta \mathbf{b}_{gi} - \mathbf{b}_{g_k} - \mathbf{n}_{g_{k+i}} - \mathbf{T}_g \mathbf{a}_{k+i}) \\ \mathbf{a}_{k+i} &= {}^I_a \mathbf{RD}_a ({}^a \mathbf{a}_{m_{k+i}} - \mathbf{b}_{a_{k+i}} - \mathbf{n}_{a_{k+i}}) \\ &= {}^I_a \mathbf{RD}_a ({}^a \mathbf{a}_{m_{k+i}} - \Delta \mathbf{b}_{ai} - \mathbf{b}_{a_k} - \mathbf{n}_{a_{k+i}})\end{aligned}$$

Note that the ω_{k+i} and \mathbf{a}_{k+i} are actually function of \mathbf{x}_{in} and \mathbf{x}_{b_k} . The angular velocity and linear acceleration can be written as:

$$\begin{aligned}\hat{\omega}_{k+i} &= {}^I_w \hat{\mathbf{R}}_D {}^w (\omega_{m_{k+i}} - \Delta \hat{\mathbf{b}}_{gi} - \hat{\mathbf{b}}_{g_k} - \hat{\mathbf{T}}_g \hat{\mathbf{a}}_{k+i}) \\ \hat{\mathbf{a}}_{k+i} &= {}^I_a \hat{\mathbf{R}}_D {}^a (\mathbf{a}_{m_{k+i}} - \Delta \hat{\mathbf{b}}_{ai} - \hat{\mathbf{b}}_{a_k})\end{aligned}$$

Let's first define the error states for the ω_{k+i} and \mathbf{a}_{k+i} as:

$$\begin{aligned}\tilde{\mathbf{a}}_{k+i} &= {}^I_a \mathbf{RH}_{Da} \tilde{\mathbf{x}}_{Da} - [\hat{\mathbf{a}}_{k+i}]_a {}^I_a \mathbf{R} \delta \theta_{Ia} \\ &\quad - {}^I_a \mathbf{RD}_a (\tilde{\mathbf{b}}_{a_k} + \Delta \tilde{\mathbf{b}}_{ai} + \mathbf{n}_{a_{k+i}}) \\ \tilde{\omega}_{k+i} &= {}^I_w \hat{\mathbf{R}}_D {}^w \tilde{\mathbf{x}}_{Dw} - {}^I_w \mathbf{RD}_w \mathbf{T}_g {}^I_a \mathbf{RH}_{Da} \tilde{\mathbf{x}}_{Da} \\ &\quad - [\hat{\omega}_{k+i}]_w {}^I_w \mathbf{R} \delta \theta_{Iw} + {}^I_w \mathbf{RD}_w \mathbf{T}_g [\hat{\mathbf{a}}_{k+i}]_a {}^I_a \mathbf{R} \delta \theta_{Ia} \\ &\quad - {}^I_w \mathbf{RD}_w \mathbf{H}_{Tg} \tilde{\mathbf{x}}_{Tg} - {}^I_w \mathbf{RD}_w \\ &\quad \left(\tilde{\mathbf{b}}_{g_k} + \Delta \tilde{\mathbf{b}}_{gi} + \mathbf{n}_{g_{k+i}} - \mathbf{T}_g {}^I_a \mathbf{RD}_a (\tilde{\mathbf{b}}_{a_k} + \Delta \tilde{\mathbf{b}}_{ai} + \mathbf{n}_{a_{k+i}}) \right)\end{aligned}$$

Hence, we can have:

$$\begin{aligned}\begin{bmatrix} \tilde{\omega}_{k+i} \\ \tilde{\mathbf{a}}_{k+i} \end{bmatrix} &\triangleq \mathbf{H}_b^{wa} \begin{bmatrix} \Delta \tilde{\mathbf{b}}_{gi} \\ \Delta \tilde{\mathbf{b}}_{ai} \end{bmatrix} + \mathbf{H}_{b_k}^{wa} \begin{bmatrix} \tilde{\mathbf{b}}_{g_k} \\ \tilde{\mathbf{b}}_{a_k} \end{bmatrix} \\ &\quad + \mathbf{H}_{in}^{wa} \begin{bmatrix} \tilde{\mathbf{x}}_{Dw} \\ \tilde{\mathbf{x}}_{Da} \\ \tilde{\mathbf{x}}_{Tg} \\ \delta \theta_{Iw} \\ \delta \theta_{Ia} \end{bmatrix} + \mathbf{H}_n^{wa} \begin{bmatrix} \mathbf{n}_{g_{k+i}} \\ \mathbf{n}_{a_{k+i}} \end{bmatrix}\end{aligned}\quad (149)$$

with:

$$\mathbf{H}_b^{wa} = \begin{bmatrix} -{}^I_w \mathbf{RD}_w & {}^I_w \mathbf{RD}_w \mathbf{T}_g {}^I_a \mathbf{RD}_a \\ \mathbf{0}_3 & -{}^I_a \mathbf{RD}_a \end{bmatrix}\quad (150)$$

$$\mathbf{H}_{b_k}^{wa} = \begin{bmatrix} -{}^I_w \mathbf{RD}_w & {}^I_w \mathbf{RD}_w \mathbf{T}_g {}^I_a \mathbf{RD}_a \\ \mathbf{0}_3 & -{}^I_a \mathbf{RD}_a \end{bmatrix}\quad (151)$$

$$\mathbf{H}_n^{wa} = \begin{bmatrix} -{}^I_w \mathbf{RD}_w & {}^I_w \mathbf{RD}_w \mathbf{T}_g {}^I_a \mathbf{RD}_a \\ \mathbf{0}_3 & -{}^I_a \mathbf{RD}_a \end{bmatrix}\quad (152)$$

$$\mathbf{H}_{in} = [\mathbf{H}_{xw} \quad \mathbf{H}_{xa} \quad \mathbf{H}_{gs} \quad \mathbf{H}_{Iw} \quad \mathbf{H}_{Ia}] \quad (153)$$

$$\mathbf{H}_{xw} = \begin{bmatrix} {}^I_w \hat{\mathbf{R}}_D {}^w \mathbf{H}_{Dw} \\ \mathbf{0}_3 \end{bmatrix}\quad (154)$$

$$\mathbf{H}_{xa} = \begin{bmatrix} -{}^I_w \mathbf{RD}_w \mathbf{T}_g {}^I_a \mathbf{RH}_{Da} \\ {}^I_a \mathbf{RH}_{Da} \end{bmatrix}\quad (155)$$

$$\mathbf{H}_{gs} = \begin{bmatrix} -{}^I_w \mathbf{RD}_w \mathbf{H}_{Tg} \\ \mathbf{0}_3 \end{bmatrix}\quad (156)$$

$$\mathbf{H}_{Ia} = \begin{bmatrix} {}^I_w \mathbf{RD}_w \mathbf{T}_g [\hat{\mathbf{a}}_{k+i}]_a {}^I_a \mathbf{R} \\ -[\hat{\mathbf{a}}_{k+i}]_a {}^I_a \mathbf{R} \end{bmatrix}\quad (157)$$

$$\mathbf{H}_{Iw} = \begin{bmatrix} -[\hat{\omega}_{k+i}]_w {}^I_w \mathbf{R} \\ \mathbf{0}_3 \end{bmatrix}\quad (158)$$

B Linearization Prediction

$\mathbf{R}_{i,i+1}$ from Eq. (49), can be written as:

$$\mathbf{R}_{i,i+1} \simeq \exp(\omega_{k+i} \delta t_i) = \exp((\hat{\omega}_{k+i} + \tilde{\omega}_{k+i}) \delta t_i) \quad (159)$$

$$= \exp(\hat{\theta}_{i,i+1}) \exp(\mathbf{J}_r(\hat{\theta}_{i,i+1}) \tilde{\omega}_{k+i} \delta t_i) \quad (160)$$

$\mathbf{p}_{i,i+1}$ from Eq. (50) can be written as:

$$\begin{aligned}\mathbf{p}_{i,i+1} &= \int_{t_{k+i}}^{t_{k+i+1}} \int_{t_{k+i}}^s {}^{I_{k+i}}_{I_\tau} \mathbf{R}^{I_\tau} a d\tau ds \\ &\simeq \int_{t_{k+i}}^{t_{k+i+1}} \int_{t_{k+i}}^s \exp(\omega_{k+i} \delta \tau) \mathbf{a}_{k+i} d\tau ds \\ &= \int_{t_{k+i}}^{t_{k+i+1}} \int_{t_{k+i}}^s \exp((\hat{\omega}_{k+i} + \tilde{\omega}_{k+i}) \delta \tau) (\hat{\mathbf{a}}_{k+i} + \tilde{\mathbf{a}}_{k+i}) d\tau ds \\ &\simeq \underbrace{\int_{t_{k+i}}^{t_{k+i+1}} \int_{t_{k+i}}^s \exp(\hat{\omega}_{k+i} \delta \tau) \hat{\mathbf{a}}_{k+i} d\tau ds}_{\hat{\mathbf{p}}_{i,i+1}} \\ &\quad - \underbrace{\int_{t_{k+i}}^{t_{k+i+1}} \int_{t_{k+i}}^s \exp(\hat{\omega}_{k+i} \delta \tau) [\hat{\mathbf{a}}_{k+i}] \mathbf{J}_r(\omega_{k+i} \delta \tau) \delta \tau d\tau ds}_{\Xi_4} \tilde{\omega}_{k+i} \\ &\quad + \underbrace{\int_{t_{k+i}}^{t_{k+i+1}} \int_{t_{k+i}}^s \exp(\hat{\omega}_{k+i} \delta \tau) d\tau ds}_{\Xi_2} \tilde{\mathbf{a}}_{k+i}\end{aligned}$$

$\mathbf{v}_{i,i+1}$ from Eq. (51) can be written as:

$$\begin{aligned}\mathbf{v}_{i,i+1} &= \int_{t_{k+i}}^{t_{k+i+1}} {}^{I_{k+i}}_{I_\tau} \mathbf{R}^{I_\tau} a d\tau \\ &\simeq \int_{t_{k+i}}^{t_{k+i+1}} \exp(\omega_{k+i} \delta \tau) \mathbf{a}_{k+i} d\tau \\ &= \int_{t_{k+i}}^{t_{k+i+1}} \exp((\hat{\omega}_{k+i} + \tilde{\omega}_{k+i}) \delta \tau) (\hat{\mathbf{a}}_{k+i} + \tilde{\mathbf{a}}_{k+i}) d\tau \\ &\simeq \underbrace{\int_{t_{k+i}}^{t_{k+i+1}} \exp(\hat{\omega}_{k+i} \delta \tau) \hat{\mathbf{a}}_{k+i} d\tau}_{\hat{\mathbf{v}}_{i,i+1}}\end{aligned}$$

$$\begin{aligned}
& - \underbrace{\int_{t_{k+i}}^{t_{k+i+1}} \exp(\hat{\omega}_{k+i}\delta\tau) [\hat{\mathbf{a}}_{k+i}] \mathbf{J}_r(\hat{\omega}_{k+i}\delta\tau) \delta\tau d\tau \hat{\omega}_{k+i}}_{\Xi_3} \\
& + \underbrace{\int_{t_{k+i}}^{t_{k+i+1}} \exp(\hat{\omega}_{k+i}\delta\tau) d\tau \hat{\mathbf{a}}_{k+i}}_{\Xi_1}
\end{aligned}$$

The block Jacobians for Eq. (83) are written as:

$$\Phi_{i,i+1} = \begin{bmatrix} \Phi_{nn} & \mathbf{H}_{wa} \mathbf{H}_b^{wa} \\ \mathbf{0}_{6 \times 9} & \mathbf{I}_6 \end{bmatrix} \quad (161)$$

$$\Phi_{nn} = \begin{bmatrix} \hat{\mathbf{R}}_{i,i+1}^\top & \mathbf{0}_3 & \mathbf{0}_3 \\ -\Delta \hat{\mathbf{R}}_i [\hat{\mathbf{p}}_{i,i+1}] & \mathbf{I}_3 & \mathbf{I}_3 \delta t_i \\ -\Delta \hat{\mathbf{R}}_i [\hat{\mathbf{v}}_{i,i+1}] & \mathbf{0}_3 & \mathbf{I}_3 \end{bmatrix} \quad (162)$$

$$\mathbf{H}_{wa} = \begin{bmatrix} \mathbf{J}_r(\theta_{i,i+1}) \delta t_i & \mathbf{0}_3 \\ -\Delta \hat{\mathbf{R}}_i \Xi_4 & \Delta \hat{\mathbf{R}}_i \Xi_2 \\ -\Delta \hat{\mathbf{R}}_i \Xi_3 & \Delta \hat{\mathbf{R}}_i \Xi_1 \end{bmatrix} \quad (163)$$

$$\Phi_b = \begin{bmatrix} \mathbf{H}_{wa} \mathbf{H}_b^{wa} \\ \mathbf{0} \end{bmatrix}, \quad \Phi_{in} = \begin{bmatrix} \mathbf{H}_{wa} \mathbf{H}_{in}^{wa} \\ \mathbf{0} \end{bmatrix} \quad (164)$$

$$\mathbf{G}_i = \begin{bmatrix} \mathbf{H}_{wa} \mathbf{H}_n^{wa} & \mathbf{0}_{9 \times 6} \\ \mathbf{0}_{6 \times 6} & \mathbf{I}_6 \delta t_i \end{bmatrix} \quad (165)$$

The biases or IMU intrinsics Jacobians can be recursively computed as:

$$\frac{\partial \begin{bmatrix} \delta \Delta \theta_{i+1} \\ \Delta \tilde{\mathbf{p}}_{i+1} \\ \Delta \tilde{\mathbf{v}}_{i+1} \end{bmatrix}}{\partial \tilde{\mathbf{x}}_*} = \Phi_{nn} \frac{\partial \begin{bmatrix} \delta \Delta \theta_i \\ \Delta \tilde{\mathbf{p}}_i \\ \Delta \tilde{\mathbf{v}}_i \end{bmatrix}}{\partial \tilde{\mathbf{x}}_*} + \mathbf{H}_{wa} \mathbf{H}_*^{wa} \quad (166)$$

where $*$ denotes b_k or in . Then, these Jacobians can be rewritten as:

$$\begin{aligned}
\frac{\partial \delta \Delta \theta_{i+1}}{\partial \tilde{\mathbf{x}}_*} &= \hat{\mathbf{R}}_{i,i+1}^\top \frac{\partial \delta \Delta \theta_i}{\partial \tilde{\mathbf{x}}_*} + [\mathbf{J}_r(\theta_{i,i+1}) \delta t_i \quad \mathbf{0}_3] \mathbf{H}_*^{wa} \\
\frac{\partial \Delta \tilde{\mathbf{p}}_{i+1}}{\partial \tilde{\mathbf{x}}_*} &= -\Delta \hat{\mathbf{R}}_i [\hat{\mathbf{p}}_{i,i+1}] \frac{\partial \delta \Delta \theta_i}{\partial \tilde{\mathbf{x}}_*} + \frac{\partial \Delta \tilde{\mathbf{p}}_i}{\partial \tilde{\mathbf{x}}_*} + \frac{\partial \Delta \tilde{\mathbf{v}}_i}{\partial \tilde{\mathbf{x}}_*} \delta t_i \\
&\quad + [-\Delta \hat{\mathbf{R}}_i \Xi_4 \quad \Delta \hat{\mathbf{R}}_i \Xi_2] \mathbf{H}_*^{wa} \\
\frac{\partial \Delta \tilde{\mathbf{v}}_{i+1}}{\partial \tilde{\mathbf{x}}_*} &= -\Delta \hat{\mathbf{R}}_i [\hat{\mathbf{v}}_{i,i+1}] \frac{\partial \delta \Delta \theta_i}{\partial \tilde{\mathbf{x}}_*} + \frac{\partial \Delta \tilde{\mathbf{v}}_i}{\partial \tilde{\mathbf{x}}_*} \\
&\quad + \Delta \hat{\mathbf{R}}_i [-\Xi_3 \quad \Xi_1] \mathbf{H}_*^{wa}
\end{aligned}$$

C State Transition Matrix

The state transition of Φ_B and Φ_A have the same structure. We can grab the gyroscope part of Φ_B to get Φ_G . Therefore, only Φ_B is shown in this paper for clarity. The Φ_I is:

$$\Phi_I = \begin{bmatrix} \Phi_{11} & \mathbf{0}_3 & \mathbf{0}_3 & \Phi_{14} & \Phi_{15} \\ \Phi_{21} & \mathbf{I}_3 & \mathbf{I}_3 \delta t & \Phi_{24} & \Phi_{25} \\ \Phi_{31} & \mathbf{0}_3 & \mathbf{I}_3 & \Phi_{34} & \Phi_{35} \\ \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{I}_3 & \mathbf{0}_3 \\ \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{I}_3 \end{bmatrix} \quad (167)$$

where we have:

$$\begin{aligned}
\Phi_{11} &= \mathbf{I}_{k+1}^{\hat{\mathbf{R}}} \\
\Phi_{21} &= -[{}^G \hat{\mathbf{p}}_{I_{k+1}} - {}^G \hat{\mathbf{p}}_{I_k} - {}^G \hat{\mathbf{v}}_{I_k} \delta t_k - \frac{1}{2} {}^G \mathbf{g} \delta t_k^2] {}^G \hat{\mathbf{R}} \\
\Phi_{31} &= -[{}^G \hat{\mathbf{v}}_{I_{k+1}} - {}^G \hat{\mathbf{v}}_{I_k} - {}^G \mathbf{g} \delta t_k] {}^G \hat{\mathbf{R}}
\end{aligned}$$

$$\begin{aligned}
\Phi_{14} &= -\mathbf{J}_r \delta t_k {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_w \\
\Phi_{24} &= {}^G \hat{\mathbf{R}} \Xi_4 {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_w \\
\Phi_{34} &= {}^G \hat{\mathbf{R}} \Xi_3 {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_w \\
\Phi_{15} &= \mathbf{J}_r \delta t_k {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_w \hat{\mathbf{T}}_g {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_a \\
\Phi_{25} &= -{}^G \hat{\mathbf{R}} \left(\Xi_4 {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_w \hat{\mathbf{T}}_g + \Xi_2 \right) {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_a \\
\Phi_{35} &= -{}^G \hat{\mathbf{R}} \left(\Xi_3 {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_w \hat{\mathbf{T}}_g + \Xi_1 \right) {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_a
\end{aligned}$$

Note that $\mathbf{J}_r \triangleq \mathbf{J}_r(\hat{\theta}_{k,k+1})$. The Φ_{in} is:

$$\Phi_{in} = \begin{bmatrix} \Phi_{in11} & \Phi_{in12} & \Phi_{in13} & \Phi_{in14} \\ \Phi_{in21} & \Phi_{in22} & \Phi_{in23} & \Phi_{in24} \\ \Phi_{in31} & \Phi_{in23} & \Phi_{in33} & \Phi_{in34} \\ \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_3 \\ \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_3 \end{bmatrix} \quad (168)$$

where we have:

$$\begin{aligned}
\Phi_{in11} &= \mathbf{J}_r \delta t_k {}^I \hat{\mathbf{R}} \mathbf{H}_{D_w} \\
\Phi_{in21} &= -{}^G \hat{\mathbf{R}} \Xi_4 {}^I \hat{\mathbf{R}} \mathbf{H}_{D_w} \\
\Phi_{in31} &= -{}^G \hat{\mathbf{R}} \Xi_3 {}^I \hat{\mathbf{R}} \mathbf{H}_{D_w} \\
\Phi_{in12} &= -\mathbf{J}_r \delta t_k {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_w \hat{\mathbf{T}}_g {}^I \hat{\mathbf{R}} \mathbf{H}_{D_a} \\
\Phi_{in22} &= {}^G \hat{\mathbf{R}} \left(\Xi_2 + \Xi_4 {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_w \hat{\mathbf{T}}_g \right) {}^I \hat{\mathbf{R}} \mathbf{H}_{D_a} \\
\Phi_{in32} &= {}^G \hat{\mathbf{R}} \left(\Xi_1 + \Xi_3 {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_w \hat{\mathbf{T}}_g \right) {}^I \hat{\mathbf{R}} \mathbf{H}_{D_a} \\
\Phi_{in13} &= -\mathbf{J}_r \delta t_k {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_w \mathbf{H}_{T_g} \\
\Phi_{in23} &= {}^G \hat{\mathbf{R}} \Xi_4 {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_w \mathbf{H}_{T_g} \\
\Phi_{in33} &= {}^G \hat{\mathbf{R}} \Xi_3 {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_w \mathbf{H}_{T_g} \\
\Phi_{in14} &= \mathbf{J}_r \delta t_k {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_w \hat{\mathbf{T}}_g [{}^I \hat{\mathbf{a}}] {}^I \hat{\mathbf{R}} \\
\Phi_{in24} &= -{}^G \hat{\mathbf{R}} \left(\Xi_2 + \Xi_4 {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_w \hat{\mathbf{T}}_g \right) [{}^I \hat{\mathbf{a}}] {}^I \hat{\mathbf{R}} \\
\Phi_{in34} &= -{}^G \hat{\mathbf{R}} \left(\Xi_1 + \Xi_3 {}^I \hat{\mathbf{R}} \hat{\mathbf{D}}_w \hat{\mathbf{T}}_g \right) [{}^I \hat{\mathbf{a}}] {}^I \hat{\mathbf{R}}
\end{aligned}$$

D Measurement Jacobians

Jacobians of camera measurements are computed as:

$$\begin{aligned}
\mathbf{H}_{CB} &= \mathbf{H}_{\mathbf{p}_f} {}^I \hat{\mathbf{R}} {}^G \hat{\mathbf{R}}^\top [{}^G \mathbf{p}_f - {}^G \mathbf{p}_I] {}^G \hat{\mathbf{R}} \quad -\mathbf{I}_3 \quad \mathbf{0}_{3 \times 30} \\
\mathbf{H}_{CC} &= [\mathbf{H}_{CCEx} \quad \mathbf{H}_{CCin}] \\
\mathbf{H}_{CF} &= \mathbf{H}_{\mathbf{p}_f} {}^I \hat{\mathbf{R}} {}^G \hat{\mathbf{R}}^\top \\
\mathbf{H}_{CCEx} &= \mathbf{H}_{\mathbf{p}_f} {}^I \hat{\mathbf{R}} {}^G \hat{\mathbf{R}}^\top \\
&\quad [\mathbf{H}_{CC1} \quad \mathbf{H}_{CC2} \quad \mathbf{H}_{CC3} \quad \mathbf{H}_{CC4} \quad \mathbf{H}_{CC5} \quad \mathbf{H}_{CC6}] \\
\mathbf{H}_{CC1} &= \mathbf{0}_{3 \times 7} \\
\mathbf{H}_{CC2} &= \mathbf{0}_{3 \times 4} \\
\mathbf{H}_{CC3} &= [{}^G \mathbf{p}_f - {}^G \mathbf{p}_I - {}^G \mathbf{R}^I \hat{\mathbf{p}}_C] \\
\mathbf{H}_{CC4} &= -{}^G \hat{\mathbf{R}} \\
\mathbf{H}_{CC5} &= {}^G \mathbf{v}_I - [{}^G \mathbf{p}_f - {}^G \mathbf{p}_I] {}^G \hat{\mathbf{R}}^I \omega \\
\mathbf{H}_{CC6} &= \frac{m}{M} \mathbf{H}_{CC5} \\
\mathbf{H}_{CCin} &= \frac{\partial \tilde{\mathbf{z}}_C}{\partial \tilde{\mathbf{x}}_{Cin}}
\end{aligned}$$

The measurement Jacobians for auxiliary IMU constraints are computed as:

$$\mathbf{H}_{AB} = \begin{bmatrix} {}^I \hat{\mathbf{R}} & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_{3 \times 21} \\ {}^G \hat{\mathbf{R}} [{}^I \hat{\mathbf{p}}_{I_a}] & -\mathbf{I}_3 & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_{3 \times 21} \end{bmatrix}$$

$$\mathbf{H}_{AA} = \begin{bmatrix} -\mathbf{I}_3 & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_{3 \times 21} \\ \mathbf{0}_3 & \mathbf{I}_3 & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_{3 \times 21} \end{bmatrix}$$

$$\mathbf{H}_{AC} = \begin{bmatrix} \mathbf{I}_3 & \mathbf{0}_3 & -I_a \boldsymbol{\omega} & \mathbf{0}_{3 \times 20} \\ \mathbf{0}_3 & -G_I \hat{\mathbf{R}} & G \mathbf{v}_I + G_I \hat{\mathbf{R}} [I \boldsymbol{\omega}]^I \mathbf{p}_{I_a} & \mathbf{0}_{3 \times 20} \end{bmatrix}$$

The measurement Jacobians for auxiliary gyroscope constraints are computed as:

$$\mathbf{H}_{GB} = \begin{bmatrix} I_g \hat{\mathbf{R}} & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_3 & \mathbf{0}_{3 \times 6} \end{bmatrix}$$

$$\mathbf{H}_{GG} = \begin{bmatrix} -\mathbf{I}_3 & \mathbf{0}_3 \end{bmatrix}$$

$$\mathbf{H}_{GC} = \begin{bmatrix} \mathbf{0}_{3 \times 7} & \mathbf{I}_3 & -I_g \hat{\boldsymbol{\omega}} & \mathbf{0}_{3 \times 8} & \mathbf{0}_{3 \times 8} \end{bmatrix}$$